

PRODUCT SPECIFICATIONS

7281DG and 7281DS DuraTech 3-way Self Retracting Lifeline with Retrieval Winch

DuraTech SRL-R's deliver reliable dual-mode operation as a Self Retracting Lifeline to arrest the forces of a fall and, as a Retrieval Winch for emergency rescue. Machined aluminum housing and drum with bronze pawls and dual brake discs provide the rugged service you expect from DuraTech SRL-R's

Features:

- Galvanized Steel Cable with internal inertial brake system
- Cable Lifeline features Load-indicating swivel Carabiner on the Harness attachment-end
- Includes mounting bracket for Davit Mast installation and storage bag

Material Specifications		
Cable:	3/16" Galvanized Steel 7 x 19 Construction	3,400 lbs. Min. Static Strength
Connector:	Plated Alloy Steel	5,000 lbs. Min. Static Strength with 3,600 lbs. Gate Strength
Housing and Drum:	Machined Aluminum Alloy	

Performance Specifications	
Static Strength:	3,000 lbs. Min.
Max. Arrest Distance:	54" or less
Average Arrest Force:	1,125 lbs. or less
Max. Arrest Force:	1,800 lbs.
SRD Class:	ANSI Class B
User Capacity:	130 to 310 lbs. Max.

Specified SRL-R Part #s		
Part #	Length	Cable Material
7281DG	60'	Galvanized Steel
7281DS	60'	Stainless Steel

Relevant Standards	
ANSI:	Z359.14-2014
OSHA:	1926.502 and 1910.66



WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never connect an Energy Absorbing Lanyard to Hip D-Rings.