











## Air Inlets and Vents

Animal confinement facilities require weather-proof inlets and vents to maintain healthy and comfortable environments. Choose from Schaefer's wide selection of cost effective, long-lived, polyethylene roof, ceiling and wall inlets and vents.

	Model	Description	CFM@ 0.125" S.P.	Rough-in Size (Width x Height)
	<b>RV-3000</b>	<b>High Volume Roof/Ridge Inlet &amp; Exhaust Vent</b> <ul style="list-style-type: none"> <li>Exhausts hot air in the summer; an inlet for fresh air in the winter</li> <li>One-piece molded polyethylene construction with UV protection for long life.</li> <li>Installs on roofs with pitches from 2/12 to 6/12.</li> <li>Downward facing bird-screened inlets protected from rain and snow.</li> <li>Inlets remain functional despite snow drifts up to 14" deep.</li> </ul>	3000	11-1/2" x 47" 
	<b>CI-1300</b>	<b>Ceiling Inlet</b> <ul style="list-style-type: none"> <li>Draws fresh air from above an interior ceiling.</li> <li>Mounts flush with ceiling and extends 16" into attic.</li> <li>Durable polyethylene housing with insulated damper doors.</li> <li>Damper doors are normally closed; they open wider with higher airflow.</li> <li>Fits between 16" or 24" ceiling joists.</li> </ul>	1350	13-1/2" x 22-3/4" 
	<b>HI-1000P</b>	<b>Hall Inlet</b> <ul style="list-style-type: none"> <li>Designed to control airflow between 2 interior spaces.</li> <li>Mounts flush to an interior wall up to 6" thick.</li> <li>Durable polyethylene housing with insulated damper door and air deflectors adjust airflow volume and direction with the seasons.</li> </ul>	1000	22-3/8" x 11-1/4" 
	<b>WI-1000P</b>	<b>Wall Inlet</b> <ul style="list-style-type: none"> <li>Draws outside air through walls up to 8" thick.</li> <li>Mounts flush to an interior wall.</li> <li>Durable polyethylene housing with insulated damper door and air deflectors adjust airflow volume and direction with the seasons.</li> <li>Weatherhood protects bird screened inlet from the elements.</li> </ul>	1000	22-5/8" x 11-1/2" 
	<b>WI-2000P</b>	<b>Wall Inlet</b> <ul style="list-style-type: none"> <li>Draws outside air through walls up to 6" thick.</li> <li>Mounts flush to an interior wall.</li> <li>Durable polyethylene housing with insulated damper door and air-stop door adjust airflow volume and direction with the seasons.</li> <li>Weatherhood protects bird screened inlet from the elements.</li> </ul>	2000	22-3/4" x 19" 



[Schaefer WI 2000p Poly Wall Air Intake Inlet 2000 CFM](#)

[Schaefer WI 1000p Poly Wall Air Intake Inlet 1000 CFM](#)

[Schaefer HI 1000p Hallway Interior Wall Air Intake Inlet 1000 CFM](#)

[Schaefer CI 1300 Ceiling Air Intake Inlet 1350 CFM](#)

[Schaefer RV3000 Roof Air Intake Exhaust Vent 3000 CFM](#)