

VAF3000A-2

Americ Confined Space Ventilator 2 Speed



Able to Ship Small Parcel :	Yes	Guard Material & Coating :	Powder Coated Steel
Blade Color :	Black	Guard Spacing (inches) :	1/2 OSHA
Blade Material :	Polypropylene	Housing Color :	Blue
Brand :	Schaefer	Housing Material :	Polyethylene
CFM (free air) :	2780	Maximum Duct Length (feet) :	125
CFM (high) :	2780	Maximum Static Pressure (in. H2O) :	3
CFM (low) :	1875	Nameplate Amps :	10/6.7
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Number of Wings :	7
CFM Range (Free Air) :	2501 - 5000	Oscillating :	No
CFM/Watt (free Air) :	3.6	Phase :	1
CFM/Watt Range (free air) :	<10	Power (hp) :	1
Component Certifications :	Motor - UL/CSA	Product Certifications :	cULus
Cord :	Included - Wired	Product Color :	Blue
Cord Length (feet) :	20	Product Dimensions (L x W x H inches) :	21" x 17" x 14"
Country of Origin :	US	Product Weight (pounds) :	33
Description :	Industrial Ventilator 12" 115V 60Hz 1Ph 2-Speed	RPM 50 Hz Motor :	2000-2600
Diameter (inches) :	12	RPM 60 Hz Motor :	3000-3600
Distinguishing Feature - Fan :	Suitable with Ducting	Schaefer Performance Test No. :	0789 / 0790
Drive Type :	Direct	Sound Level (dBA @ 10') :	82
Fixed or Portable :	Portable	Speeds :	2
Frequency (Hz) :	60	Switch :	On product
Guard Color :	Black	Voltage :	115