

## VK20-CK-WSC

### 20" Cattle Kooler Circulation Fan



Air Velocity (@ 5 times diameter) :	1220	Fixed or Portable :	Fixed
BESS Lab Performance Test No. :	12371	Frequency (Hz) :	60
Blade Color :	Metallic	Guard Color :	White
Blade Material :	Aluminum	Guard Material & Coating :	Powder Coated Steel
Brand :	Schaefer	Guard Spacing (inches) :	1/2 - 1 UL507
CFM (free air) :	5470	Nameplate Amps :	3.8/1.9
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Number of Wings :	3
CFM Range (Free Air) :	5001 - 10000	Oscillating :	No
CFM/Watt (free Air) :	15.6	Phase :	1
CFM/Watt Range (free air) :	15.1 - 20	Power (hp) :	1/3
Component Certifications :	Motor - UL/CSA	Product Color :	White
Cord :	Included - Wired	Speed Control Compatible :	No
Cord Length (feet) :	7	Speeds :	1
Country of Origin :	US	Switch :	On cord
Description :	Fan Circulation 20" Versa-Kool w/Tapered Guards, Cord, CK Mount & Wired Switch Cord	VFD Compatible :	No
Diameter (inches) :	20	Voltage :	115/230
Drive Type :	Direct		