

# MECHANICALS

When there is no margin for error on your jobsite, *FallTech* Self-Retracting Lifelines are the best choice in Deceleration Devices. SRL's have a long life, are consistently reliable and dramatically reduce arresting forces and deceleration distances, minimizing the risks of serious injuries during a fall.

*FallTech's* SRL's have earned an excellent reputation in the industry and are known to be tough and reliable. We go the extra mile by utilizing the highest quality components available and by integrating premium features as standard. Load-indicating swivel snap hooks, tag-lines and buffer assemblies, just to name a few.

We also have a complete line of equipment to facilitate Confined Space entry, retrieval and rescue. Our tripods feature rugged, lightweight aluminum construction and have an excellent range of adjustability to ensure maximum stability. When coupled with our winch platform, entry and retrieval are a snap.

Our 3-way SRL's provide that extra margin of safety during Confined Space operations and are equipped with an auxiliary winch to provide a quick and simple mode of rescue in the event that a fall occurs. These recovery devices are built on the same chasis as our *DuraTech* series cable SRL's and are among the best available.

*FallTech* has one of the most aggressive service, repair and re-certification programs in the industry to ensure that your equipment is in top working-order and that your workers make it home at the end of the day. As with everything we do, it isn't just a matter of protecting the bottom line...it's just the right thing to do.



**NetZeroTools**  
800-577-6389  
[www.netzerotools.com](http://www.netzerotools.com)

# Confined Space

FallTech's Confined Space assortment has all the elements needed to perform entry, retrieval and rescue effectively and safely. These products are tried, tested and engineered to last.



## 7500 Confined Space Kit

- #7275 Confined Space Tripod.
- #7285 *DuraTech* 3-Way SRL and Mounting Bracket.
- #7280 Tripod Bag (See Page 34).
- #7282 Equipment Bag (See Page 34).

**7500S: 7500 with Stainless Steel Cable in 3-Way.**

## 7505 Confined Space Kit

- #7275 Confined Space Tripod.
- #7290 60' Winch and Mounting Bracket.
- #7280 Tripod Bag (See Page 34).
- #7282 Equipment Bag (See Page 34).

**7505S: 7500 with Stainless Steel Cable in Winch.**

**7510: 7500 with #7295 120' Winch.**



## 7275 Confined Space Tripod

- Adjustable from 6' to 11' in Height with 4' and 11' Spans Between the Feet at Minimum and Maximum Height.
- Cast Aluminum Head has an Integral Stainless Steel Pully to Accommodate a Winch or an SRL.
- Cast Aluminum Head also has Three Alloy-Steel Hangers to Allow for the Mounting of Additional Pulleys or Equipment.
- Telescoping Legs Constructed from Tubular Aluminum Extrusion.
- Cast Aluminum Feet have Rubber Treads for Secure Placement and a Ratcheting Web Strap for Additional Security.
- Meets the Requirements of OSHA 1926 and ANSI Z359-1.1992(R1999).



## 7285 60' *DuraTech* 3-Way Recovery Unit

- 3/16" Galvanized Steel Cable has a Tensile Strength of 4,000 lbs.
- Aluminum Housing and Drum are Durable, Lightweight and Resistant to Corrosion.
- Hard-Wearing Bronze Pawls and Ratchet Center.
- Housing Features Built-In Carry Handle.
- High-Strength Aluminum Alloy Main Shaft for Lighter Weight.
- Spring and Ball Buffer Assembly Prevent Lock-Up from Free-Wheeling.
- In SRL Mode, Arrest Forces are Reduced to 900 lbs. or Less.
- Winch Mechanism can be Activated for Emergency Rescue/Retrieval (Rated for Personnel Only).
- Includes Free Tag Line to Prevent Free-Wheeling.
- Features the *DuoTech* Load-Indicating Swivel Snap Hook for Back D-Ring Attachment.
- Includes Tripod Mounting Bracket.
- Weighs only 37 lbs.
- Meets the Requirements of OSHA 1926 and ANSI Z359-1.1992(R1999).

**7285S: 7285 with Stainless Steel Cable.**

**7286: Tripod Mounting Bracket (Available Separately).**



## 7287 82' 3-Way Recovery Unit

- 3/16" Galvanized Steel Cable has a Tensile Strength of 4,000 lbs.
- Aluminum Housing and Drum are Durable, Lightweight and Resistant to Corrosion.
- Hard-Wearing Bronze Pawls and Ratchet Center.
- Housing Features Built-In Carry Handle.
- Buffer Assembly Prevents Lock-Up from Free-Wheeling.
- In SRL Mode, Arrest Forces are Reduced to 900 lbs. or less.
- Winch Mechanism can be Activated for Emergency Rescue/Retrieval (Rated for Personnel Only).
- Includes Free Tag Line to Prevent Free-Wheeling.
- Features the *DuoTech* Load-Indicating Swivel Snap Hook for Back D-Ring Attachment.
- Includes Tripod Mounting Bracket.
- Weighs 50 lbs.
- Meets the Requirements of OSHA 1926 and ANSI Z359-1.1992(R1999).

**7287S: 7287 with Stainless Steel Cable.**

**7288: 138' 3-Way Recovery Unit.**

**7288S: 7288 with Stainless Steel Cable.**

**7289: Tripod Mounting Bracket (Available Separately).**



## 7290 60' Personal Winch Confined Space Kit

- 3/16" Galvanized Steel Cable has a Tensile Strength of 4,000 lbs.
- Fully Compatible with 7275 Confined Space Tripod.
- Includes Tripod Mounting Bracket.
- Fully Rated for Personnel and Equipment.
- #7275 Confined Space Tripod.
- For Use in Confined Space Entry and Retrieval.

7290S: 7287 with Stainless Steel Cable.

7295: 120' Personnel Winch, Galvanized Steel Cable.

7295S: 7295 with Stainless Steel Cable.



# Confined Space

## 7421 Aluminum Pulley

- Anodized Aluminum Frame and Wheel.
- Mounts and Locks Using Standard Carabiner.
- Designed for Use with 3/8" or Smaller Cable.
- Has a Tensile Strength of 5,000 lbs.
- Compatible with *FallTech* SRL's and Winches.



## 7280 Tripod Bag

- Filament-Reinforced Nylon Fabric is Resistant to Tears and Abrasion.
- Heavy-Duty Zipper for Long Life.
- Dual Handles for Easy Team-Lift.
- Measures 80"L x 11" W x 11" H.



## 7282 Tripod Bag

- Filament-Reinforced Nylon Fabric is Resistant to Tears and Abrasion.
- Heavy-Duty Zipper for Long Life.
- Heavy-Duty Web Carry Handles and Shoulder Strap.
- Measures 20"L x 10"W x 12"H.




# SRL'S *Features & Benefits*



**CNC Machined  
Aluminum Housing**




**CNC Machined  
Aluminum Drum**



**Precision Internal Parts**



**Twin Ferrules with  
Steel Thimbles**



**Spring and Ball  
Buffer Assembly**



**SRL Tag Line  
Prevents  
free-wheeling and  
lock-up**



**Load-Indicating  
Snap Hook**