

The Bimmer Baron E36 OBC Delete Panel - Installation Instructions

Thank you for your purchase of an E36 OBC delete panel! At 24 grams, this is a nearly weightless way to delete a broken or unwanted OBC without leaving an ugly hole in your dash. Please read this entire instruction manual before beginning installation; improper installation WILL lead to damaging the panel. Now onto the instructions:

1. Disconnect the battery (optional). Removing the OBC with the battery connected could cause possible damage. If your OBC is already removed or if you don't care about possibly damaging it, skip this step.
2. Remove the OBC. This is most easily done by pushing on the back of it through the hole in the top of your cubby hole until it pops out. Disconnect the wiring connectors and tuck them behind the dash. If you ordered any parts from us that snap into the cubby hole assembly, remove the cubby hole and install the parts now.
3. Cock the cubby hole assembly forward, as pictured below.



4. Rest your delete panel in the hole with the top all the way forward and with the bottom resting on the cocked cubby hole, as pictured below. Make sure the bottom tabs are lined

up with the holes on the top of the cubby. It's important to do it this way as the upper retainers are not meant to be bent and WILL break if you install it improperly.



5. Push forward on both the cubby and the delete panel at the point they meet, ensuring the bottom tabs stay correctly aligned with the holes they'll be resting in. Keep pushing with light pressure until both parts snap into place. There may be some misaligned or "off" edges, simply push on them and wiggle both pieces around until everything is flush and

aligned.



Congratulations, you're finished! Enjoy your new OBC replacement!