



MINI SHOT M-SPEC SERIES

FEATURES

- Low-power consumption with 12-hour auto shut off
- Quick and easy windage and elevation adjustments with any flat head tool
- 3 MOA red dot reticle with 10 brightness levels
- User friendly ambidextrous digital switch brightness controls
- Built to last, lightweight and rugged steel protective shield, IP67 waterproof with scratch resistant lens coating
- Night vision compatible
- Motion activated on/off function

SPECIFICATIONS

	SM26043 (DE)	SM26043-LQD (DE)
Reticle type	3 MOA	3 MOA
Reticle color	Red	Red
Magnification (x)	1	1
Objective lens dimensions (mm)	21 x 15	21 x 15
Elevation adjustment range (MOA)	110	110
Windage adjustment range (MOA)	110	110
Adjustment value (one click =)	1 MOA	1 MOA
Parralax setting	25yd - ∞	25yd - ∞
Battery type	CR1632	CR1632
Battery life (hours)	300 - 30,000	300 - 30,000
Length w/ low mount (in/mm)	1.73 / 44	2.2 / 56
Width w/ low mount (in/mm)	1.14 / 29	1.85 / 47
Height w/ low mount (in/mm)	1.34 / 34	1.34 / 34
Weight w/ low mount (oz)	2.3	2.7
Length w/ riser mount (in/mm)	1.73 / 44	2.2 / 56
Width w/ riser mount (in/mm)	1.14 / 29	1.85 / 47
Height w/ riser mount (in/mm)	2.2 / 56	2.2 / 56
Weight w/ riser mount (oz)	3	3.4

The Sightmark Mini M-Spec LQD DE is an ideal optic for tactical simulations, competition shooting and home defense. The Mini M-Spec in dark earth features a steel protective shield, making the 2.3 ounce Mini one of the most reliable compact sized optics available. The kit includes a low-profile locking quick detach mount for pistols and shotguns along with a riser mount for AR platform rifles. Use the Mini M-Spec DE in virtually any environment, from daytime to low-light conditions complete with a 3 MOA red dot reticle with added ambidextrous switch controls to benefit both left- and right-handed when adjusting through 10 brightness levels. Mini M-Specs boast a coated and scratch resistant lens, features a low consumption battery life of 300-30,000 hours on a single CR1632, 12-hour auto shut-off and is IP67 rated waterproof, dustproof and shockproof.

