

SIGHT MARK®



Wolverine FSR Reflex Sight

SPECIFICATIONS

Reticle type	2 MOA Dot
Reticle color	Red
Illuminated reticle (yes/no)	yes
Brightness settings	Off, NV1, NV2, 3-10
Magnification (x)	1
Objective aperture (mm)	28
Window material	glass
Eye relief (mm)	unlimited
Elevation adjustment (MOA)	120
Windage adjustment (MOA)	120
Finish/color	Matte Black
Body material	Aluminum 6061-T6 / Rubber
Maximum recoil (G's)	800
IP rating (waterproof)	IP67 - submersible to 1m / 3ft
Shockproof (yes/no)	yes
Fog proof (yes/no)	yes
Lens coatings	AR red
Mount type	picatinny
Battery type	AA
Battery life (hours)	900-1,000,000/50,000 setting 6
Battery voltage (V)	1.5V
Operating temperature (F°)	-22 to 122
Dimensions	4.4 x 2.9 x 2.6
Weight	12.3 oz

FEATURES

- Powered by a single AA battery
- 6 years of continuous use at power setting 6 of 10
- Digital switch brightness controls
- Scratch resistant, anti-reflective lens coating
- 28mm objective lens for quicker acquisition
- Protected adjustment caps
- Rubber armored, single piece 6061-T6 aluminum housing
- Adjustable mount height
- IP67 waterproof rating - submersible to 1m/3ft
- Fogproof, nitrogen purged
- Night vision compatible
- Unlimited eye relief
- Shockproof design
- Wide range of operating temperature, -22 to 122 of

Included Accessories

- Rubber lens cover
- Picatinny mount
- Riser for absolute cowitness

The Wolverine FSR 1x28 Red Dot Sight features is designed for quick target acquisition and features a 2MOA dot reticle. One AA battery powers the Wolverine for over 1,000,000 hours on low setting and 50,000 hours on setting 6. The durable Wolverine FSR is rubber armored, waterproof, fogproof and shockproof. NV modes make it compatible with night vision devices. Ergonomic digital switch controls make the sight quick and easy to operate