SIGHT IMARK®



Ultra Shot A-Spec Reflex Sight

FFATURES

SPECIFICATIONS

Reticle type	4 Pattern - 5 MOA dot, 3 MOA dot	Rugged, lightweight aluminum alloy housing
	with 50 MOA circle, 3 MOA dot with 50 MOA crossshair, 3 MOA	Protective aluminum shield
	dot with 30 MOA circle/crosshair	 Quick detach picatinny mount
	(subtensions total 50 MOA)	 Wide lens provides quick target acquistion
Reticle color	Red	 Slotted windage and elevation adjustments
Magnification	1X	Red reticle illumination
Objective lens	33x24	Low battery indication
dimensions(mm)		Digital switch controls
Elevation adjustment range	120	 10 reticle brightness levels
(MOA)		Night vision brightness modes
Windage adjustment range	120	• 1 hour auto shutoff
(MOA)		Multiple reticle options
Adjustment value (one click=)	1 MOA	Scratch resistant lens coating
Parallax setting (yd/m)	10 / 9.1	Interlok internal locking adjustment system
Battery type	CR123A	INCLUDED ACCESSORIES
Battery life (hours)	200 - 2,000	Neoprene cover
Dimentions (in)	4.33 x 1.96 x 2.28	Adjustment tools
Weight	10.8	• Battery

Perfectly suited for fast, accurate action at the range, the Sightmark Ultra Shot A-Spec Reflex Sight delivers a crisp field of view with an advanced, anti-reflective, scratch resistant lens system, 4 red reticle options with 10 brightness settings, parallax corrected (beyond 10 yds.), 1 MOA click adjustments (120 MOA of travel), Interlok internal locking adjustment system and a long, reliable battery life, from 200 to 2,000 hours on a single CR123 battery. Built tough, the IP55 weather-resistant, shockproof Ultra Shot A-Spec Reflex boasts a 6061-T6 aircraft-grade aluminum body and protective shield, recoil rating up to .50 BMG and a lifetime warranty. Includes adjustment tools, CR123A battery, operation manual and neoprene cover. Compatible with the Sightmark XT-3 Tactical Magnifier (SM19062).

SM26032

www.sightmark.com