



SM26045

SM26046

Direct Mount

Lower Mount

Riser Mount

## MINI SHOT A-SPEC SERIES

### FEATURES

- Low-power consumption
- Quick and easy windage and elevation adjustments with any flat head tool
- 2 MOA red dot reticle with 10 brightness levels
- User friendly ambidextrous digital switch brightness controls
- Built to last, lightweight and rugged steel protective shield, IP67 waterproof with scratch resistant lens coating

### SPECIFICATIONS

	SM26045	SM26046
Reticle type	2 MOA	2 MOA
Reticle color	Red	Green
Magnification (x)	1	1
Objective lens dimensions (mm)	22 x 17	22 x 17
Elevation adjustment range (MOA)	110	110
Windage adjustment range (MOA)	110	110
Adjustment value (one click =)	1 MOA	1 MOA
Parralax setting	25yd - ∞	25yd - ∞
Battery type	CR1632	CR1632
Battery life (hours)	15 - 160	30 - 200
Length w/ low mount (in/mm)	1.854 / 47	1.854 / 47
Width w/ low mount (in/mm)	1.223 / 31	1.223 / 31
Height w/ low mount (in/mm)	1.552 / 39	1.552 / 39
Weight w/ low mount (oz)	2.3	2.3
Length w/ riser mount (in/mm)	1.854 / 47	1.854 / 47
Width w/ riser mount (in/mm)	1.223 / 31	1.223 / 31
Height w/ riser mount (in/mm)	2.195 / 55.77	2.195 / 55.77
Weight w/ riser mount (oz)	2.9	2.9

The Sightmark Mini A-Spec is an ideal optic for tactical simulations, competition shooting and home defense. The Mini A-Spec features a steel protective shield, making the 2.3 ounce Mini, one of the most reliable compact sized optics available. The kit includes a low-profile mount for pistols and shotguns along with a riser mount for AR platform rifles. Use the Mini A-Spec in virtually any environment, from daytime to low-light conditions complete with a 2 MOA red dot reticle with added ambidextrous switch controls to benefit both left- and right-handed when adjusting through 10 brightness levels. Mini A-Specs boast a coated and scratch resistant lens, features a low consumption battery life on a single CR1632, is IP67 rated waterproof, dustproof and shockproof.

