



GLADIATOR BREAKDOWN

AMP HOURS WATT HOURS CONT. AMP PEAK AMP CONT. PWR

60 MAX

60AH 3427WH 420A 630A 28KW

STANDARD
60 TOURING
S EDITION

70AH 4032WH 202A 302A 11.5KW
350A 630A 20KW

60 COMPACT

51AH 2938WH 360A 540A 24KW

60 ENDURANCE

60AH 3456WH 173A 260A 10KW

66 MAX

51AH 3305WH 420A 540A 28KW

66 COMPACT

42.5AH 2745WH 300A 450A 22KW

72 MAX

51AH 3672WH 420A 540A 30KW

STANDARD
72 TOURING
S EDITION

60AH 4320WH 173A 260A 12.5KW
300A 540A 21.5KW

72 COMPACT

38AH 2745WH 270A 405A 22KW

72 SURGE

40AH 2880WH 200A 360A 15KW



**Charged
Voltage**

**Low Voltage
Cut Off**

**Stock or
Aftermarket
Controller**

60V

67.2V

46.2V

Stock
Compatible

66V

75.6V

52.2V

Stock
Compatible

72V

84V

58V

Aftermarket
Required

SIZING (IN)

WEIGHT

**INSTALL
TIME**

**60 Max
60 Touring**

L 6
W 5.7
H 16.25

41 LBS
18.5 KG

1 HOUR,
SWAP BASE
PLATE

66 Max

L 6
W 5.7
H 16.25

40 LBS
18 KG

1 HOUR,
SWAP BASE
PLATE

**72 Max
72 Touring**

L 6
W 5.7
H 17.50

44 LBS
20 KG

1 HOUR,
SWAP BASE
PLATE

**All Compact
and Endurance**

L 6.25
W 5.5
H 16

36 LBS
16 KG

5 MINUTES,
ONLY LID
EXTENSION

72 Surge

L 6.25
W 5.5
H 13.7

33 LBS
15 KG

DROP IN