

TECHNICAL DETAILS

westex.

FLOORING EXCELLENCE

ULTIMA TWIST COLLECTION



westex.
DYE SERVICE

Create your own
bespoke colour with
our unique dye service





westex.
DYE SERVICE

Create your own
bespoke colour with
our unique dye service

ULTIMA TWIST COLLECTION



Ultima Twist is the ideal choice for residential or contract carpeted areas, offering a superb combination of performance and comfort.

Available in 5 widths:
1.00m, 3.66m (12ft), 4.00m, 4.57m (15ft) & 5.00m

Method of Manufacture:
2 Fold Tufted Cut Pile

Pile Material:
80% Wool 20% Nylon


Colour Palette:
120 Standard Colours - Available in All 5 Qualities

IMO Certified
IMO FTP Code 2010 Part 2 & Part 5

Available on Request



5 LUXURY QUALITIES



PINNACLE



Luxury Rating: **LC5**

End Use Classification: **Class 23 / 33**

Tuft Density*: **161,200 per m²**

Total Carpet Thickness*: **11.5mm**

Tog Rating*: **1.67 tog**

CREST


Luxury Rating: **LC5**

End Use Classification: **Class 23 / 33**

Tuft Density*: **155,000 per m²**

Total Carpet Thickness*: **9.5mm**

Tog Rating*: **1.48 tog**

MAJOR


Luxury Rating: **LC4**

End Use Classification: **Class 23 / 33**

Tuft Density*: **130,200 per m²**

Total Carpet Thickness*: **9.5mm**

Tog Rating*: **1.46 tog**




ULTIMA

Luxury Rating: **LC4**

End Use Classification: **Class 23 / 33**

Tuft Density*: **120,280 per m²**

Total Carpet Thickness*: **8.5mm**

Tog Rating*: **1.29 tog**




PENULTIMA

Luxury Rating: **LC3**

End Use Classification: **Class 23 / 32**

Tuft Density*: **105,400 per m²**

Total Carpet Thickness*: **7.5mm**

Tog Rating*: **1.19 tog**



*+/- 10% commercial tolerance



Westex Carpets Limited.
Castle Mills, Moorend, Cleckheaton, West Yorkshire, BD19 3PS, United Kingdom
Tel: +44 (0)1274 861334 Fax: +44 (0)1274 873266
westexflooring.com info@westexflooring.com

westex.

FLOORING EXCELLENCE




westex.
DYE SERVICE


Create your own
bespoke colour with
our unique dye service

ULTIMA TWIST COLLECTION


120 STANDARD COLOURS



Claret




Burnt Orange



Cinnamon



Tofu



Porridge



Jasper



Classic Red



Mocha




Walnut



Cocoa



Hopsack



Tuscan Harvest



Dogwood




Spice




Springbok




Burnt Oak




Hessian




Ochre




Aston Pink




Koi




Bracken



Chestnut




Kalahari



Dijon



Bark



Squirrel




Almond



Aloe



Celeriac



Corn silk



Stone




Highland Heather




Buff



Sepia




Sand




Nectar




Paper Rose




Brandysnap




Autumn Dawn




Biscuit




Sherbet




Cookie Mix




Verglas




Honey




Pampas




Chicory




Gypsum




Grain




Limestone



Nutmeg




Alabaster




Driftwood




Oatmeal




Cream



Chalk




Sorbet



Pink Silk



Pavestone



Parchment



Maize



Westex Carpets Limited.
Castle Mills, Moorend, Cleckheaton, West Yorkshire, BD19 3PS, United Kingdom
Tel: +44 (0)1274 861334 Fax: +44 (0)1274 873266
westexflooring.com info@westexflooring.com

westex.

FLOORING EXCELLENCE



westex.
DYE SERVICE

Create your own
bespoke colour with
our unique dye service

ULTIMA TWIST COLLECTION


120 STANDARD COLOURS




Antique Gold



Bottle Green



Amazon




Nightfall



Aubergine




Black



Olive Green



Broom



Angelica




Fennel Blue




Thistle




Granite




Mistletoe




Malachite




Laurel




Gentian




Veronica




Peat




Eucalyptus



Willow




Kingfisher




Azure



Scotchmist



Ebony



Sage



Oasis Green




Bonsai




Ink




Metropolitan



Fossil




Clover




Croft Green



Peacock




Seaspray




Zinc




Anthracite




Bayleaf




Hebe




Spearmint




Bluebird



Dove Grey




Dark Slate




Shadow




Eau de Nil




Aquamarine



Slate Blue




Malt




Gull




Quartz




Opal




Sea Foam



Cobalt




Mercury



Ash




Fleece



White Mint



Silver Fox



Duck Egg



Wisp



Mortar
















Westex Carpets Limited.
Castle Mills, Moorend, Cleckheaton, West Yorkshire, BD19 3PS, United Kingdom
Tel: +44 (0)1274 861334 Fax: +44 (0)1274 873266
westexflooring.com info@westexflooring.com

westex.

FLOORING EXCELLENCE

Technical Specification

Luxury Rating	BS EN 1307:2014	LC5	
End Use Classification	BS EN 1307:2014	Class 23 Heavy Domestic Use Class 33 Heavy Commercial Use	
Hexapod 4000	BS EN 1307:2014	4.0	
Hexapod 12000	BS EN 1307:2014	3.0	
Roll Widths		Available in 5 sizes: • 1.00m • 3.66m (12ft) • 4.00m • 4.57m (15ft) • 5.00m	
Roll Length		Customisable (80m ² +)	
Method of Manufacture		2 Fold Tufted Cut Pile, 1/8" Gauge	
Tuft Density*	ISO 1763	161,200 per m ²	
Pile Material		80% Wool 20% Nylon	
Pile Height above Backing*		9.5mm	
Total Carpet Thickness*		11.5mm	
Primary Backing		Polypropylene	
Flammability	BS4790 Hot Nut Test	Low Radius of Char	
Reaction to Fire	BS EN 13501	Class Cfl-s1	
Delamination	BS ISO 11857	Pass Minimum 15.00 (N)	
Thermal resistance	BS4745	1.67 tog	
Dimensional Stability	ISO 2551-1981 (2010)	Pass Pass if shrinkage is equal to or less than 1.2% and extension less than or equal to 0.5%	
Colour Fastness: Light Colour Fastness: Shampooing Colour Fastness: Rubbing	BS EN ISO -B02 BS ISO -18168 BS EN ISO -X12	4-5 4 4	
Electrical Resistance	ISO 10965:2011	Pass Does not exceed 10Ω	
Sound Absorption		Class C with Underlay	
Underfloor heating system		Suitable to a max. 27°C Please check with manufacturers guidelines	
Guarantee		6 Years	
IMO Certified	IMO FTP Code 2010 Part 2 & Part 5	Pass Available on request	
CE Mark	EN 14041		

*Commercial Tolerance +/- 10%
















Westex Carpets Limited.
Castle Mills, Moored, Cleckheaton, West Yorkshire, BD19 3PS, United Kingdom
Tel: +44 (0)1274 861334 Fax: +44 (0)1274 873266
westexflooring.com info@westexflooring.com



FLOORING EXCELLENCE

Technical Specification

Luxury Rating	BS EN 1307:2014	LC5	
End Use Classification	BS EN 1307:2014	Class 23 Heavy Domestic Use Class 33 Heavy Commercial Use	
Hexapod 4000	BS EN 1307:2014	4.0	
Hexapod 12000	BS EN 1307:2014	3.0	
Roll Widths		Available in 5 sizes: • 1.00m • 3.66m (12ft) • 4.00m • 4.57m (15ft) • 5.00m	
Roll Length		Customisable (80m ² +)	
Method of Manufacture		2 Fold Tufted Cut Pile, 1/8" Gauge	
Tuft Density*	ISO 1763	155,000 per m ²	
Pile Material		80% Wool 20% Nylon	
Pile Height above Backing*		7.5mm	
Total Carpet Thickness*		9.5mm	
Primary Backing		Polypropylene	
Flammability	BS4790 Hot Nut Test	Low Radius of Char	
Reaction to Fire	BS EN 13501	Class Cfl-s1	
Delamination	BS ISO 11857	Pass Minimum 15.00 (N)	
Thermal resistance	BS4745	1.48 tog	
Dimensional Stability	ISO 2551-1981 (2010)	Pass Pass if shrinkage is equal to or less than 1.2% and extension less than or equal to 0.5%	
Colour Fastness: Light Colour Fastness: Shampooing Colour Fastness: Rubbing	BS EN ISO -B02 BS ISO -18168 BS EN ISO -X12	4-5 4 4	
Electrical Resistance	ISO 10965:2011	Pass Does not exceed 10Ω	
Sound Absorption		Class C with Underlay	
Underfloor heating system		Suitable to a max. 27°C Please check with manufacturers guidelines	
Guarantee		6 Years	
IMO Certified	IMO FTP Code 2010 Part 2 & Part 5	Pass Available on request	
CE Mark	EN 14041		















*Commercial Tolerance +/- 10%



Westex Carpets Limited.
 Castle Mills, Moorend, Cleckheaton, West Yorkshire, BD19 3PS, United Kingdom
 Tel: +44 (0)1274 861334 Fax: +44 (0)1274 873266
 westexflooring.com info@westexflooring.com



Technical Specification

Luxury Rating	BS EN 1307:2014	LC4	
End Use Classification	BS EN 1307:2014	Class 23 Heavy Domestic Use Class 33 Heavy Commercial Use	 
Hexapod 4000	BS EN 1307:2014	4.0	
Hexapod 12000	BS EN 1307:2014	3.0	
Roll Widths		Available in 5 sizes: • 1.00m • 3.66m (12ft) • 4.00m • 4.57m (15ft) • 5.00m	
Roll Length		Customisable (80m ² +)	
Method of Manufacture		2 Fold Tufted Cut Pile, 1/8" Gauge	
Tuft Density*	ISO 1763	130,200 per m ²	
Pile Material		80% Wool 20% Nylon	
Pile Height above Backing*		7.5mm	
Total Carpet Thickness*		9.5mm	
Primary Backing		Polypropylene	
Flammability	BS4790 Hot Nut Test	Low Radius of Char	
Reaction to Fire	BS EN 13501	Class Cfl-s1	
Delamination	BS ISO 11857	Pass Minimum 15.00 (N)	
Thermal resistance	BS4745	1.46 tog	
Dimensional Stability	ISO 2551-1981 (2010)	Pass Pass if shrinkage is equal to or less than 1.2% and extension less than or equal to 0.5%	
Colour Fastness: Light Colour Fastness: Shampooing Colour Fastness: Rubbing	BS EN ISO -B02 BS ISO -18168 BS EN ISO -X12	4-5 4 4	
Electrical Resistance	ISO 10965:2011	Pass Does not exceed 10Ω	
Sound Absorption		Class C with Underlay	
Underfloor heating system		Suitable to a max. 27°C Please check with manufacturers guidelines	
Guarantee		6 Years	
IMO Certified	IMO FTP Code 2010 Part 2 & Part 5	Pass Available on request	
CE Mark	EN 14041		















*Commercial Tolerance +/- 10%



Westex Carpets Limited.
Castle Mills, Moored, Cleckheaton, West Yorkshire, BD19 3PS, United Kingdom
Tel: +44 (0)1274 861334 Fax: +44 (0)1274 873266
westexflooring.com info@westexflooring.com



Technical Specification

Luxury Rating	BS EN 1307:2014	LC4	
End Use Classification	BS EN 1307:2014	Class 23 Heavy Domestic Use Class 33 Heavy Commercial Use	 
Hexapod 4000	BS EN 1307:2014	4.0	
Hexapod 12000	BS EN 1307:2014	3.0	
Roll Widths		Available in 5 sizes: • 1.00m • 3.66m (12ft) • 4.00m • 4.57m (15ft) • 5.00m	
Roll Length		Customisable (80m ² +)	
Method of Manufacture		2 Fold Tufted Cut Pile, 1/8" Gauge	
Tuft Density*	ISO 1763	120,280 per m ²	
Pile Material		80% Wool 20% Nylon	
Pile Height above Backing*		6.5mm	
Total Carpet Thickness*		8.5mm	
Primary Backing		Polypropylene	
Flammability	BS4790 Hot Nut Test	Low Radius of Char	
Reaction to Fire	BS EN 13501	Class Cfl-s1	
Delamination	BS ISO 11857	Pass Minimum 15.00 (N)	
Thermal resistance	BS4745	1.29 tog	
Dimensional Stability	ISO 2551-1981 (2010)	Pass Pass if shrinkage is equal to or less than 1.2% and extension less than or equal to 0.5%	
Colour Fastness: Light Colour Fastness: Shampooing Colour Fastness: Rubbing	BS EN ISO -B02 BS ISO -18168 BS EN ISO -X12	4-5 4 4	
Electrical Resistance	ISO 10965:2011	Pass Does not exceed 10Ω	
Sound Absorption		Class C with Underlay	
Underfloor heating system		Suitable to a max. 27°C Please check with manufacturers guidelines	
Guarantee		6 Years	
IMO Certified	IMO FTP Code 2010 Part 2 & Part 5	Pass Available on request	
CE Mark	EN 14041		














*Commercial Tolerance +/- 10%



Westex Carpets Limited.
Castle Mills, Moored, Cleckheaton, West Yorkshire, BD19 3PS, United Kingdom
Tel: +44 (0)1274 861334 Fax: +44 (0)1274 873266
westexflooring.com info@westexflooring.com



Technical Specification

Luxury Rating	BS EN 1307:2014	LC3	
End Use Classification	BS EN 1307:2014	Class 23 Heavy Domestic Use Class 32 General Commercial Use	
Hexapod 4000	BS EN 1307:2014	3.5	
Hexapod 12000	BS EN 1307:2014	2.5	
Roll Widths		Available in 5 sizes: • 1.00m • 3.66m (12ft) • 4.00m • 4.57m (15ft) • 5.00m	
Roll Length		Customisable (80m ² +)	
Method of Manufacture		2 Fold Tufted Cut Pile, 1/8" Gauge	
Tuft Density*	ISO 1763	105,400 per m ²	
Pile Material		80% Wool 20% Nylon	
Pile Height above Backing*		5.5mm	
Total Carpet Thickness*		7.5mm	
Primary Backing		Polypropylene	
Flammability	BS4790 Hot Nut Test	Low Radius of Char	
Reaction to Fire	BS EN 13501	Class Cfl-s1	
Delamination	BS ISO 11857	Pass Minimum 15.00 (N)	
Thermal resistance	BS4745	1.19 tog	
Dimensional Stability	ISO 2551-1981 (2010)	Pass Pass if shrinkage is equal to or less than 1.2% and extension less than or equal to 0.5%	
Colour Fastness: Light Colour Fastness: Shampooing Colour Fastness: Rubbing	BS EN ISO -B02 BS ISO -18168 BS EN ISO -X12	4-5 4 4	
Electrical Resistance	ISO 10965:2011	Pass Does not exceed 10Ω	
Sound Absorption		Class C with Underlay	
Underfloor heating system		Suitable to a max. 27°C Please check with manufacturers guidelines	
Guarantee		6 Years	
IMO Certified	IMO FTP Code 2010 Part 2 & Part 5	Pass Available on request	
CE Mark	EN 14041		

*Commercial Tolerance +/- 10%



Westex Carpets Limited.
Castle Mills, Moored, Cleckheaton, West Yorkshire, BD19 3PS, United Kingdom
Tel: +44 (0)1274 861334 Fax: +44 (0)1274 873266
westexflooring.com info@westexflooring.com





westex.
DYE SERVICE

own your colour.

We are very proud of our extensive standard colourbank, which we consider to be second to none. We also offer you limitless bespoke colours, as we have our own Dye House and control the whole manufacturing process. Special Dyes must meet your approval before full production is started.*

THE UNIQUE ADVANTAGES OF A WESTEX CARPET



Allergy Guard

Allergy Guard protects against pests, bacteria and allergens whilst Fresh Guard inhibits mould and neutralises pet odours. All Westex Carpets have an anti-dust mite treatment applied to protect against house dust mites, mould fungi and bacteria and their allergens, fresh guard is also part of the construction of this treatment.

The active ingredient in the treatment does not allow the debris (human skin, hair etc.) to decay into the food that the dust mites thrive upon, thus there is no environment for them to exist or thrive in. This will also inhibit the bacteria and mould development. Thorough vacuuming will then maintain the cleanliness of the carpet.



Fresh Guard

This treatment has been subjected to the full rigours of scientific testing, both toxicologically and ecologically, to establish that there is no harm to human or pet health, or the environment. It is tested to OECD 404 and 406 to qualify as no irritation or sensitisation.

These treatments combine with the wool fibre on a permanent basis and will last the life time of the carpet.



Stain-Resist

All Westex Carpets have a Stain Resist treatment applied. Stain Resist is not a stain blocker. Stain Resist slows the stain penetration down, giving time to get the carpet cleaned. The stain resist formula bonds with the fibre to provide protection against dirt and damp, therefore making caring for the carpet easier.

This treatment prevents stains from penetrating the fiber and they temporarily remain locked on the surface so they can easily be removed. The breathable properties of the fibre are not affected.

Shampooing and professional carpet cleaning products cannot break the bonds between the active chemical and fibre. The performance of the Stain Resist will last 5 years, subject to normal, reasonable use.


Stain Resist is free from CFCs and is dermatologically tested. The Stain Resist polymers show no toxicity even at the highest applied levels and no bioavailability, metabolism or hydrolysis.



Moth Guard

All Westex carpets have a mothproofing treatment applied. Mothproofing protects your carpet against the attack of both moths and other wool eating insects. The active ingredient in the moth-proof makes the keratin (a protein found in wool) that moths, bugs and other insects thrive upon, indigestible. They literally starve as their digestive systems are unable to convert the keratin they have eaten into usable food.

The moth-proof combines with the wool fibre on a permanent basis and will last the life time of the carpet. Westex's award winning moth-proof process has had scientific testing, both toxicologically and ecologically, to establish that there is no harm to human or pet health with no effluent waste.



*A minimum order quantity of 40m² in any one width applies.



Westex Carpets Limited.
Castle Mills, Moorend, Cleckheaton, West Yorkshire, BD19 3PS, United Kingdom
Tel: +44 (0)1274 861334 Fax: +44 (0)1274 873266
westexflooring.com info@westexflooring.com

westex.

FLOORING EXCELLENCE