



TOPOIL[®] HIGH SOLID

Oil-wax wood finish



3025
Natural



3026
Acacia



3056
Clear matt



PRODUCT DESCRIPTION

Osmo TopOil is a special oil and wax combination, used as a treatment on wooden kitchen work top surfaces and general interior joinery. It is made on a base of natural plant oils and waxes. The surface will be protected against common household substances such as wine, beer, fizzy drinks, coffee, tea, fruit juices, milk and water. When dry, the finish is safe for humans, animals and plants and is suitable for childrens' toys as per EN 71.3 (European norm) and fast to perspiration and saliva. Oils like the TopOil 3056 clear emphasise the natural colour of the wood (wet-look effect).

RECOMMENDED USE

Osmo TopOil is ideal for the protection of furniture surfaces and work surfaces made of solid wood or edge-glued panels (e.g. kitchen worktops, desks, shelving etc.) in indoor areas. Also suitable for cork and OSB.

CONTAINS

Solid ingredients: Based on natural vegetable oils (sunflower-oil, thistle-oil and soyabean-oil) and waxes (carnauba wax and candelilla wax), silica, paraffins, lead-free siccatives (drying agents) and water-repellent additives; disaromatized white spirit (benzene-free). Complies with Environment Canada VOC regulations (SOR/2009-264). Detailed declaration of ingredients available upon request.

TECHNICAL DATA

Specific gravity: 0.92-0.97 g/cm³
Viscosity: 50-70s DIN EN ISO 2431/4 mm, thixotropic
Odour: faint/mild, after drying odourless
Flash point: >60°C acc. DIN EN ISO 2719

STORAGE

Shelf-life is 5 years or more if can is tightly closed.

SURFACE PREPARATION

The wooden surface must be clean and dry (max. 20 % moisture content). Clean or lightly sand old microporous stains. Remove old varnishes. If necessary sand down the surface using fine sandpaper (grit P120-150), carefully remove dust. Always wear a dust mask when sanding.

DIRECTIONS FOR USE

Osmo TopOil is ready to use. Please do not thin. Shake well before use. Apply thinly with a cloth, following the grain of the wood. Leave to dry overnight for at least 8 - 10 hours. Allow for good ventilation. Repeat 2 - 3 times as described above and allow to dry for 8 - 10 hours between the applications. The finished surface is, among other things, influenced by the woods natural characteristics, therefore a trial application is required before finishing.

CLEANING YOUR TOOLS

Use Osmo Brush Cleaner and Thinner (benzene-free).

DRYING TIME

Approx. 8-10 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Ventilate well while drying.



COVERAGE

1 litre covers approx. 258-516 ft² (24-48 m²) with one coat. Coverage depends significantly on the condition of the wood. All information refers to smooth and planed/sanded surfaces. Other surfaces may lead to differences in coverage.

NOTE

TopOil 3056 Clear enhances the tone of wood (permanent wet effect).

TopOil 3025 Natural counteracts exactly this effect and protects wood nearly invisibly. The natural colour tone of wood is preserved.

On dark/reddish wood species, TopOil 3068 Natural is visible as slightly white chalky surface.

TopOil 3026 Acacia is lightly pigmented, which gives the wood an elegant look.

Applying the product too generously and insufficient ventilation lead to delays in drying time.

For cabinet interiors and drawers, apply max. one coat thinly with a cloth. Allow for good ventilation while drying.

If a higher gloss level is desired, after thoroughly drying apply Osmo Liquid Wax Cleaner (also available as Spray) thinly and polish when dry. Wood surfaces treated with TopOil are easy to maintain. Remove coarse dirt with a broom or a vacuum cleaner. To clean, add Osmo Wash and Care concentrate to mop water and clean the surface with a damp (not wet!) cloth.

Use Osmo Liquid Wax Cleaner to remove tough stains, which cleans and regenerates the surface at the same time.

HAZARD STATEMENTS



CAUTION

READ INSTRUCTIONS BEFORE USING

DANGER OF COMBUSTION. Do not get in eyes. Do not get on skin or clothing. Keep out of reach of children. Use only in a well-ventilated area. Keep away from flames or sparks. Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.

FIRST AID TREATMENT. Contains aliphatic hydrocarbons. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

DISPOSAL

Dispose of contents/container in accordance with national regulations.

COLOUR TONES

3025 Natural
3026 Acacia
3056 Clear matt

CAN SIZES

0.5 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 10/17