



TEAK-OIL SPRAY

Easy to use and high coverage
- penetrates deeply into wood!



008 Clear



1 APPLICATION

PRODUCT DESCRIPTION

Clear, water and dirt-repelling oil to protect and maintain garden furniture and decking. Osmo Teak-Oil Spray penetrates deeply into the wood surfaces, regulates thereby moisture and prevents swelling and shrinkage. The microporous oil coating will not crack, peel or flake. To refresh, simply reapply (No sanding – no dust!).

RECOMMENDED USE

Osmo Teak-Oil Spray protects, maintains and improves the appearance of garden furniture made of Teak and other hardwoods – in covered outdoor areas. It is also well-suited for the clear treatment of garden furniture and other similarly used surfaces.

CONTAINS

Based on natural plant oils (sunflower oil, soya oil and thistle oil), siccatives (drying agents) and water-repelling additives. Dearomatized white spirit (benzene-free). Detailed declaration of ingredients available upon request.

TECHNICAL DATA

Specific gravity: 0.85-0.9 g/cm³

Viscosity: not applicable

Odour: characteristic

Flash point: not applicable, aerosol

STORAGE

Up to 2 years and longer if can is kept dry and closed tightly.

SURFACE PREPARATION

Wood surface must be clean, dry and frost-free (moisture content max. 20%). Osmo Teak-Oil Spray is ready to use.

Shake spray can well and carry out trial spray.

Clean old microporous stains thoroughly. Old paints and lacquers must be completely removed. As a general rule, wear a dust mask during sanding works.

Hardwoods with an especially high content of natural wood extractives need to weather off (for approx. 4 weeks) or be degreased with Osmo Brush Cleaner and Thinner.

The finished surface is influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

DIRECTIONS FOR USE

Spraying distance approx. 25 cm. Afterwards rub in with a brush.

While applying, cover and protect surrounding areas and parts that should not be treated against the spray mist. Wipe away any excess with a cloth.

Allow to dry for approx. 12 hours under good ventilation and apply a second coat.

When renovating, one coat applied is usually sufficient.

Clean spray nozzle after use.

CLEANING OF TOOLS

With Osmo Brush Cleaner and Thinner (free of aromatic compounds).

DRYING TIME

Approx. 12 hours (normal climatic conditions, 73°F (23 °C)/50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time.

Ventilate well while drying.



COVERAGE

1 litre covers approx. 269ft² (25 m²) with one application. Coverage depends significantly on the condition of the wood. All information refers to smooth and planed/sanded surfaces. Other surfaces may lead to differences in coverage.

NOTE

Osmo Teak-Oil Spray is clear and therefore does not protect against UV radiation from the sun (greying). If the original colour tone of freshly sawn wood should be preserved (e.g. Bangkirai), we recommend a coat of Osmo Decking-Oils in a natural shade in the appropriate colour tone.

DANGER

EXTREME DANGER

VERY FLAMMABLE

CONTENTS UNDER PRESSURE

CONTENTS MAY CATCH FIRE. CONTAINER MAY EXPLODE IF HEATED. Do not puncture. Do not burn. Do not smoke. Do not get in eyes. Do not get on skin or clothing. Keep out of reach of children. Use only in a well-ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Store away from heat.

FIRST AID TREATMENT. Contains aliphatic hydrocarbons. If swallowed, call a Poison Control Centre or doctor immediately.

Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines. Only completely emptied cans can be recycled.

COLOUR TONE

008 Clear

CAN SIZES

0.4 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 10/18