

DURABLE CAST IRON RADIATORS

DIMENSIONS • RATINGS

Cast Tube

FREE STANDING CAST IRON RADIATORS

WEIGHT/LB.
PER SECTION
Approx.

Cast Tube 4 x 19	7¼
Cast Tube 4 x 25	8½
Cast Tube 6 x 25	13¾

ACCESSORIES

PART #

1" Push Nipples	TPN1
1" Plug	TP1
1 ¼" Plug	TP114
2" Pedestal	PED2
3" Pedestal	PED3

Ratings SQ. FT./EDR

NO. OF SECTIONS LENGTH 1¾" PER SECTION 19" HEIGHT 1.6SQ.FT. PER SECTION 25" HEIGHT 2.0 SQ.FT. PER SECTION 25" HEIGHT 3.0 SQ.FT. PER SECTION

STOCK	4	7.0"	6.4" T4194	8	T4254	12	T6254
	6	10.5"	9.6" T4196	12	T4256	18	T6256
	8	14.0"	12.8" T4198	16	T4258	24	T6258
	10	17.5"	16.0" T41910	20	T42510	30	T62510
	12	21.0"	19.2" T41912	24	T42512	36	T62512
	14	24.5"	22.4" T41914	28	T42514	42	T62514
	16	28.0"	25.6" T41916	32	T42516	48	T62516
	18	31.5"	28.8" T41918	36	T42518	54	T62518
	20	35.5"	32.0" T41920	40	T42520	60	T62520
	22	38.5"	35.2" T41922	44	T42522	66	T62522
	24	42.0"	38.4" T41924	48	T42524	72	T62524
	26	45.5"	41.6" T41926	52	T42526	78	T62526
	28	49.0"	44.8" T41928	56	T42528	84	T62528
	30	52.5"	48.0" T41930	60	T42530	90	T62530
	32	56.0"	51.2" T41932	64	T42532	96	T62532
	34	59.5"	54.4" T41934	68	T42534	102	T62534
	36	63.0"	57.6" T41936	72	T42536	108	T62536
	38	66.5"	60.8" T41938	76	T42538	114	T62538
	40	70.0"	64.0" T41940	80	T42540	120	T62540
	42	73.0"	67.2" T41942	84	T42542	126	T62542
SPECIAL ORDER	44	77.0"	70.4" T41944	88	T42544	132	T62544

NOTE: HEAT EMISSION - BASED ON 240 BTU (STEAM) PER SQUARE FOOT PER HOUR
MAXIMUM WORKING PRESSURE: 15 LBS. STEAM, 30 LBS. WATER



6 x 25


4 x 25

4 x 19

AV. WATER TEMP. IN RADIATOR	220°	215°	210°	200°	190°	180°	170°	160°	150°
HEAT EMISSION BTU PER SQ. FT.	250	240	230	210	190	170	150	130	110

4x19	0.08 Gallons Per Section
4x25	0.12 Gallons Per Section
6x25	0.17 Gallons Per Section

Dimensions



SIZE	A	B&C	D	E	*F
4x19	15 7/16"	4 1/2"	2 11/16"	19"	17 13/16"
4x25	21 7/16"	4 1/2"	2 11/16"	25"	23 13/16"
6x25	21 7/16"	6 7/8"	2 11/16"	25"	23 13/16"

* LEGLESS - OVERALL HEIGHT. TAPPING - TOP-1" BOTTOM-1¼"
ADD ½" TO LENGTH FOR EACH BUSHING.
END SECTION REGULARLY SUPPLIED WITH 1" TOP TAPPING AND 1¼" BOTTOM TAPPINGS.
NOTE: CAST TUBE RADIATORS ARE SOLD IN EVEN * NUMBER OF SECTIONS UP TO A MAXIMUM OF 44 SECTIONS. FOR ASSEMBLIES FROM 26 TO 44 SECTIONS, ONE EXTENDED CENTER LEG SECTION IS FURNISHED.
ODD SIZES AVAILABLE UPON REQUEST