

PRODUCT DATA SHEET 06.23





HEAVY-DUTY HURRICANE GROUND ANCHORS

69

DEFINING **FEATURES**

INCLUDES:

- Very heavy-duty design
- 3 different lengths available
- Re-usable
- Holding capacities from 5.60kn to 12.60kn

ADDITIONAL FEATURES/INFORMATION:

Installation Advice;

Rotate clockwise to insert. Hurricane anchor must be fully inserted up to the disc to achieve maximum strength rating.







ADDITIONAL FEATURES

- Anchor Dimensions:
 - A Wire 12mm diameter
 - B Loop 60mm diameter
 - © Disc measurements 100mm x 4mm
 - Blade to blade distance 73mm
 - **€** Center pin diameter − 16mm
- Very heavy duty steel structure to ensure maxium strength and longevity.
- Powder coated for advanced material protection.



OFTEN USED WITH







1



YE-299



TAKING SAFETY TO NEW HEIGHTS



ORDERING INFORMATION

PART NO	SHAFT LENGTH	TOTAL LENGTH	STRENGTH RATING	MATERIAL	UNIT WEIGHT
AF-6300-500	500mm	590mm	560kg/5.6kn	Steel	1.52kg
AF-6300-650	650mm	740mm	960kg/9.6kn		1.90kg
AF-6300-900	900mm	990mm	1,260/12.6kn		2.44kg

SUITABLE INDUSTRIES

















SCAFFOLDING

OIL & GAS

CONSTRUCTION

ROOFING

BRICKWORK

DEMOLITION

TRANSPORTATION

MAINTENANCE

TAKING SAFETY TO NEW HEIGHTS



DISTRIBUTED BY:

LEACH'S

Beacon Park, 228 Holme Lacy Road, Hereford HR2 6BQ Tel: 01432 346800 Email: sales@leachs.com First for Safety www.leachs.com



