

# PRODUCT DATA SHEET 05.23



3

N

4

TWIN TAILED WEBBING FALL ARREST LANYARD

# DEFINING **FEATURES**

#### **INCLUDES:**

- 100kg User Weight
- Available in 3 lengths
- Includes Steel Gear Locking ScaffHook & Screw Gate Carabina
- Manufactured from Low Stretch Polyester Webbing
- Individually Serial Numbered

#### **CONFORMITY:**

EN355







# ADDITIONAL FEATURES



 Steel Gear Locking ScaffHook

Material: Aluminium Opening: 60mm Static Strength: 20kN Lock Type: 2 Stage Gear Lock



Steel Locking Carabina Material: Steel Opening: 18mm Static Strength: 25kN Lock Type: Screw Gate



Webbing Connection Point Protectors to ensure longevity.



Sewn Polyester Webbing

for better performance in rugged and challenging environments. Low stretch Non-slip Higher Abrasion-resistance Lightweight



Shockpack With Clear Protective Casing

for additional protection of shock-absorber and product information including: individual serial number, date of manufacture and conformity.





TAKING SAFETY TO NEW HEIGHTS

# COMPATIBLE ATTACHMENTS & ACCESSORIES

## **ATTACHMENTS**

## **ALL BIG**BEN **HARNESSES**












### **SUITABLE FOR USE WITH**









# ORDERING INFORMATION

PART NO	LENGTH	WEBBING TYPE	WIDTH	SCAFFHOOK MATERIAL	CARABINA MATERIAL	UNIT WEIGHT
FP-4492-150	1.5m	Straight	30mm	Steel	Steel	1.56kg
FP-4492-175	1.75m	Straight	30mm	Steel	Steel	1.56kg
FP-4492	2m	Straight	30mm	Steel	Steel	1.58kg

## **SUITABLE INDUSTRIES**

















SCAFFOLDING

OIL & GAS

CONSTRUCTION

ROOFING

BRICKWORK

DEMOLITION

TRANSPORTATION

MAINTENANCE

TAKING SAFETY TO NEW HEIGHTS



DISTRIBUTED BY:

#### LEACH'S

Beacon Park, 228 Holme Lacy Road, Hereford HR2 6BQ Tel: 01432 346800 Email: sales@leachs.com First for Safety www.leachs.com



