

PRODUCT DATA SHEET 03.23



3

0

2

4

FALL RESTRAINT WEBBING LANYARD

DEFINING **FEATURES**

INCLUDES:

- Includes 2 Steel Carabinas
- Available in 3 lengths
- Manufactured from Low stretch Polyester Webbing
- Individually Serial Numbered

CONFORMS TO:

EN354

EN358

ADDITIONAL FEATURES/INFORMATION:

This product has a life of 10 years from date of manufacture or 5 years from date of first use.







ADDITIONAL FEATURES

Steel Locking Carabina

- Material: Steel
- Opening: 18mm
- Static Strength: 25kN
- Lock Type: Screw Gate

2 Individually Serial Numbered

3 Sewn Polyester Webbing

for better performance in rugged and challenging environments.

- Low stretch
- Non-slip
- Higher abrasion resistance
- Lightweight







ORDERING INFORMATION

PART NO	LENGTH	WEBBING	CARABINA	MIN BREAKING STRENGTH	CARABINA SPECIFICATION			UNIT
					Opening	Static Strength	Lock Type	WEIGHT
FP-4502-100	100cm	Polyester	Steel	15kN	18mm	25kN	Screw Gate	500g
FP-4502-150	150cm	Polyester	Steel	15kN	18mm	25kN	Screw Gate	500g
FP-4502-200	200cm	Polyester	Steel	15kN	18mm	25kN	Screw Gate	500g

SUITABLE INDUSTRIES

















SCAFFOLDING

OIL & GAS

CONSTRUCTION

ROOFING

BRICKWORK

DEMOLITION

TRANSPORTATION

MAINTENANCE

TAKING SAFETY TO NEW HEIGHTS



DISTRIBUTED BY:

LEACH'S

Beacon Park, 228 Holme Lacy Road, Hereford HR2 6BQ Tel: 01432 346800 Email: sales@leachs.com First for Safety www.leachs.com



