

# PRODUCT DATA SHEET 03.23





FALL RESTRAINT
WEBBING LANYARD

4 5

WITH SCAFFHOOK

# DEFINING **FEATURES**

#### **INCLUDES:**

- Includes Steel Gear Locking ScaffHook & Screw Gate Carabina
- Available in 3 lengths
- Manufactured from Low stretch Polyester Webbing
- Individually Serial Numbered

#### **CONFORMITY:**

EN354

**EN358** 

## ADDITIONAL FEATURES/INFORMATION:

This product has a life of 10 years from date of manufacture or 5 years from date of first use.







#### ADDITIONAL FEATURES

#### Steel Gear Locking ScaffHook

- Material: Aluminium
- Opening: 60mm
- Static Strength: 20kN
- Lock Type: 2 Stage Gear Lock

#### Steel Locking Carabina

- Material: Steel
- Opening: 18mm
- Static Strength: 25kN
- Lock Type: Screw Gate

#### **3 Individually serial Numbered**

#### Sewn Polyester Webbing

For better performance in rugged and challenging environments.

- Low stretch
- Non-slip
- Higher Abrasion-resistance
- Lightweight







# COMPATIBLE ATTACHMENTS & ACCESSORIES

### **ATTACHMENTS**

#### **ALL BIG**BEN **HARNESSES**












#### **SUITABLE FOR USE WITH LIFELINES**









# ORDERING INFORMATION

PART NO	LENGTH	WEBBING Type	WIDTH	MIN BREAKING STRENGTH	CARABINA MATERIAL	SCAFFHOOK Material	UNIT WEIGHT
FP-4505-100	100cm	Straight	30mm	15kN	Steel	Zinc Plated Steel	710g
FP-4505-150	150cm	Straight	30mm	15kN	Steel	Zinc Plated Steel	840g
FP-4505-200	200cm	Straight	30mm	15kN	Steel	Zinc Plated Steel	920g

## **SUITABLE INDUSTRIES**

















SCAFFOLDING

OIL & GAS

CONSTRUCTION

ROOFING

BRICKWORK

DEMOLITION

TRANSPORTATION

MAINTENANCE

TAKING SAFETY TO NEW HEIGHTS



DISTRIBUTED BY:

LEACH'S

Beacon Park, 228 Holme Lacy Road, Hereford HR2 6BQ Tel: 01432 346800 Email: sales@leachs.com First for Safety www.leachs.com



