

PRODUCT DATA SHEET 01.23



ECO 2 POINT SAFETY HARNESS

ENVIRONMENTALLY FRIENDLY HARNESS

DEFINING **FEATURES**

INCLUDES:

- Front & Rear Anchorage
- Fall Indicators
- Atrium D-Rings
- Fully Adjustable Leg, Chest & Shoulder Webbing

CONFORMS TO:

EN361

Tested and approved for users up to 140kg.

RECOMMENDED LIFESPAN:

This product has a life of 10 years from date of manufacture and 5 years from date of first use.

FULLY RECYCLABLE:

This harness is certified free from harmful chemicals and uses a safe dye called OEKO-Tex (R).

It's also PFC-free and made from up-cycled PET bottles, making it 100% recyclable.



FIRST FOR SAFETY



Fully Adjustable Leg, Chest & Shoulder Straps

For compliant fitting via 5 separate buckle adjusters.



Atrium D-rings

For maximum rotational flexibility and reduced rigidity.




Webbing Manufactured from **PET bottles**

Making this a 100% recyclable safety harness.



Fall Indicators

For inspection speed and convenience (located on the rear of the harness).



Front & Rear **Anchorage Points**

For convenience in general use and rescue scenarios.



FIRST FOR QUALITY

COMPATIBLE ATTACHMENTS & ACCESSORIES

FALL ARREST



































FIRST FOR INNOVATION

ORDERING INFORMATION

PART NO	BUCKLE TYPE		ATTACHMENT POINTS		COMFORT PADS	SIZE
	Standard	Quick Release	1 Point	2 Point	CONFORT PADS	SIZE
FP-5500ECO-STD	•			•		М
FP-5500ECO-L	•			•		L
FP-5500ECO-XL	0			0		XL

SIZING CHART

SIZE	STANDARD	LARGE	X-LARGE
A	42-50"	50-54"	54-58"
CHEST	107-127cm	127-137cm	137-147cm
B	36-44"	44-48"	48-52"
Waist	91-112cm	112-122cm	122-132cm
C	44-52"	52-56"	56-60"
HIPS	112-132cm	132-142cm	142-152cm

SUITABLE INDUSTRIES



SCAFFOLDING



OIL & GAS



& GAS CONSTRUCTION



ROOFING



BRICKWORK



DEMOLITION



FIRST FOR SOLUTIONS