

PRODUCT DATA SHEET 03.23



3

6495U

BIGGUY SINGLE ELASTICATED FALL ARREST LANYARD

DEFINING **FEATURES**

INCLUDES:

- Alloy Scaff Hook
- Self-Recoiling Webbing
- Steel Locking Carabiner
- · Available in 3 lengths

CONFORMITY:

EN355

Tested and approved to a SWL of 150kg.

ADDITIONAL FEATURES/INFORMATION:

Lifespan;

This Product Has a life of 10 years from date of manufacture or 5 years from date of first use.









ADDITIONAL FEATURES

Webbing

- Conforms to: EN355
- Length Available: 1.5m, 1.75m & 2m
- Self Recoiling Technology

Carabiner

- Material: Steel
- Opening: 18mm
- Static Strength: 25kN
- Lock Type: Screw Gate

3 Scaff Hook

- Material: Aluminium
- Opening: 60mm
- Static Strength: 20kNLock Type: 2 Stage Gear Lock

Shock Pack

- Clear information for speedy access to serial number, manufacturing and expiry date.
- Protective Sleeve to preserve the shockabsorbing webbing and vital information.





TAKING SAFETY TO NEW HEIGHTS

COMPATIBLE ATTACHMENTS & ACCESSORIES

ATTACHMENTS

ALL BIGBEN **HARNESSES**











SUITABLE FOR USE WITH LIFELINES







ORDERING INFORMATION

PART NO	WEBBING TYPE	SCAFFHOOK/ Carabina	LOCK TYPE		LENGTH	SWL
			Scaffhook	Carabina	LENGIN	SWL
FP-6495U-150	Elasticated Bungee	Steel	2 Stage Gear-Lock	Screw Gate	1.50m	150kg
FP-6495U-175	Elasticated Bungee	Steel	2 Stage Gear-Lock	Screw Gate	1.75m	150kg
FP-6495U	Elasticated Bungee	Steel	2 Stage Gear-Lock	Screw Gate	2m	150kg

SUITABLE INDUSTRIES

















SCAFFOLDING

OIL & GAS

CONSTRUCTION

ROOFING

BRICKWORK

DEMOLITION

TRANSPORTATION

MAINTENANCE

TAKING SAFETY TO NEW HEIGHTS



DISTRIBUTED BY:

LEACH'S

Beacon Park, 228 Holme Lacy Road, Hereford HR2 6BQ Tel: 01432 346800 Email: sales@leachs.com First for Safety www.leachs.com



