



PRODUCT DATA SHEET 07.23



1
1
1
7
1

**ROOFING
PICK HAMMER**

MAGNETIC

DEFINING FEATURES

- Magnetic head function to hold nails in place.
- Forged from a single piece of steel
- Rubber grip handle
- Anti-shock technology

CONFORMITY:

Manufactured in accordance with DIN1193.

ADDITIONAL FEATURES/ INFORMATION:

Steel hardness of 53 HRc.



FIRST FOR SAFETY

ADDITIONAL FEATURES

- 1 Magnetic head**
is designed for very precise nail driving, including a groove to position nails prior to installation.
- 2 Monolithic construction (forged from a single piece of steel)**
to provide maximum strength.
- 3 Head incorporates nail puller and pointed claw**
for better reach and pin-point accuracy.
- 4 Anti-slip rubber grip**
with unique hold pattern.
- 5 Tether hole**
for additional safety.
- 6 Hammer heel**
includes PPE safety message for users and bystanders.



FIRST FOR QUALITY

COMPATIBLE ATTACHMENTS & ACCESSORIES

ACCESSORIES:



TS-3022SLC



LE-2320B



LE-2190



TS-3003



TS-3114

RECOMMENDED PPE:



PP-3175U



PP-3531-C

ORDERING INFORMATION

PART NO	TOTAL LENGTH	UNIT WEIGHT	MATERIAL
GT-1711	326mm	980g	Steel & Rubber

SUITABLE INDUSTRIES



SCAFFOLDING



CONSTRUCTION



ROOFING



BRICKWORK



DEMOLITION



MAINTENANCE

FIRST FOR INNOVATION

01432 346800 | sales@leachs.com | www.leachs.com