



PRODUCT DATA SHEET 10.23



1	TUFFBUCKET®
1	
2	
9	
1	

DEFINING FEATURES

- Oil, Water & Chemical Resistant
- Individually Serial Numbered
- Reinforced, Rigid Bottom
- Mechanically Integral Carry Handles
- High-Visibility Colour

CONFORMITY:

Tested to 1,504kg and approved to a SWL of 100kg.

ADDITIONAL FEATURES/ INFORMATION:

Improved Material Design:

This Leach's Lifting Bucket is manufactured from rubberised canvas in order to withstand the most demanding situations, and provide resistance to Oil, Chemicals and Water.



FIRST FOR SAFETY

ADDITIONAL FEATURES

- 1 **Manufactured from rubberised canvas** for maximum resistance to Oil, Chemicals and Water.
- 2 **Load tested to 1,540kg** giving this bucket a safety ratio factor of 15.4 to 1.
- 3 **Integral Carry Handles**
- 4 **Reinforced 300mm rigid bottom**
- 5 **Riveted & Sewn** for maximum strength.
- 6 **Individually Serial numbered** for convenient recording and traceability.



SIMILAR PRODUCTS:



LH-2906R




LH-2901K

OFTEN PURCHASED WITH:



LH-5033R



LH-3020



LH-2903

FIRST FOR QUALITY

ORDERING INFORMATION

PART NO	DIAMETER	HEIGHT	CAPACITY	SWL	RESISTANT TO	UNIT WEIGHT
LH-2911	300mm	380mm	24 litre	100kg	Oil/Chemicals/ Water	2.5kg

SUITABLE INDUSTRIES



SCAFFOLDING



OIL & GAS



CONSTRUCTION



ROOFING



BRICKWORK



DEMOLITION



TRANSPORTATION



MAINTENANCE



STADIUM & EVENTS



TV & FILM

FIRST FOR SOLUTIONS

01432 346800 | sales@leachs.com | www.leachs.com