



# PRODUCT DATA SHEET 09.23



5020

## GIN WHEEL PULLEY

### DEFINING FEATURES

- Extremely robust
- Very simple to use

#### CONFORMITY:

**BS 1692 (1998)**

Tested to 1000kg and certified  
to a SWL of 250kg.




## FIRST FOR SAFETY

## ADDITIONAL FEATURES

- 1 Robust Steel Structure
- 2 Scaffold Tube Bracket.
- 3 Rope Guide.
- 4 254mm free turning wheel



## BRAKED PULLEY'S:



LH-2919



LH-7135

FIRST FOR QUALITY

# COMPATIBLE ATTACHMENTS & ACCESSORIES

## OFTEN PURCHASED WITH:



LH-5033R



LH-3020



LH-3010



LH-2903



LH-2899



LH-2895



LH-2904



LH-2906R



LH-2906VT



LH-2911



LH-2907S

## FIXING ARMS



LH-2920A



LH-2921A

# FIRST FOR INNOVATION

## ORDERING INFORMATION

PART NO	MATERIAL	WHEEL DIAMETER	COMPATIBLE ROPE	UNIT WEIGHT
LH-5020	Steel	254mm	18mm	5kg

## SUITABLE INDUSTRIES



SCAFFOLDING



CONSTRUCTION



ROOFING



BRICKWORK



DEMOLITION



TRANSPORTATION



TV & FILM

---

# FIRST FOR SOLUTIONS

01432 346800 | sales@leachs.com | www.leachs.com