

PRODUCT DATA SHEET 06.23

WITH LARGE WHEEL



- 50% Larger Pulley Wheel
- Scaffold Tube Support Bracket
- Optional Fixing Arm
- Offset Guide Wheels
- Solid Aircraft Alloy Components
- Controlled Descent Technology

CONFORMITY:

CE MARKED

Certificated in compliance with BHSR of the EC PPE Directive (89/686/EEC) where no EN standard can be directly applied.

Tested and approved to a SWL of 50kg.

ADDITIONAL FEATURES/ INFORMATION:

Improved overall design, optimised for ease of use and to guard against damage from harsh conditions.







bigbensafety.com









6 Optional Tube Bracket for quick and convenient use with scaffolding.





(3 strand) rope.

TAKING SAFETY TO NEW HEIGHTS

bigbensafety.com





ACCESSORIES





FIXING **ARMS**









PART NO	MATERIALS		AUTO	COMPATIBLE ROPE	SWL	UNIT
	Main Housing	Other	DESCENT RATE	COWFAIIDLE NOPE	OWL	WEIGHT
LH-7135	Aircraft Alloy/Steel	Stainless & Mild Steel/Aluminimum Alloy/Silicone Bronze	1.5m/ second	16-18mm double braided /18mm polypropylene (3 strand)	50kg	7kg

SUITABLE INDUSTRIES







bigbensafety.com

DISTRIBUTED BY:

LEACH'S Beacon Park, 228 Holme Lacy Road, Hereford HR2 6BQ Tel: 01432 346800 Email: sales@leachs.com First for Safety www.leachs.com



