



PRODUCT DATA SHEET 09.23



1
6
1
1

STABILA 81SM MAGNETIC LEVEL

DEFINING FEATURES

- Strong rare-earth magnet system
- Electrostatic powder coating
- Tough cast aluminium profile



MADE IN GERMANY



FIRST FOR SAFETY

ADDITIONAL FEATURES

- 1 **Compact, tough, cast aluminium profile.**
- 2 **Slender, trapezoidal profile shape** for an optimum, easy grip.
- 3 **Strong rare-earth magnet system** for adhesion to metal objects – leaves the hands free when aligning and adjusting pillars and supports.
- 4 **With a length of only 25 cm,** the torpedo spirit level is ideally suited for applications in cramped conditions.
- 5 **Easy cleaning,** dirt can be removed thanks to the electrostatic powder coating.
- 6 **Spirit level with one precision-milled measuring surface** no discolourations on the surface.
- 7 **STABILA installation technology** ensures long-term accuracy – measuring accuracy in normal position is ± 0.5 mm/m and ± 0.75 mm/m in reverse position.
- 8 **Equipment: 1 horizontal vial, 1 vertical vial, 1 milled measuring surface, rare-earth magnet system** (up to 5 times stronger than standard ferrite magnets).

OFTEN PURCHASED WITH:



LE-2070B/LE2020N



LE-2220STB



TS-3022SLC



LE-2250SP

ORDERING INFORMATION

PART NO	OUTTER COATING	LENGTH	UNIT WEIGHT	MEASUREMENT ACCURACY		PART NO. INCLUDING NYLON HOLDER
				Normal Position	Reverse Position	
LM-1611	Electrostatic Powder Coating	25cm	220g	0.50 mm/m	0.75 mm/m	LM-1611SH

SUITABLE INDUSTRIES



SCAFFOLDING



OIL & GAS



CONSTRUCTION



ROOFING



BRICKWORK



MAINTENANCE

FIRST FOR SOLUTIONS

01432 346800 | sales@leachs.com | www.leachs.com