



PRODUCT DATA SHEET 07.23



1651RD

**RUBBER ENCLOSED
TAPE MEASURE**

5M

DEFINING FEATURES

- Shock-absorbing co-moulded rubber casing
- Non-slip grip design
- Corrosion-resistant end hook
- Double sided tape option available



FIRST FOR SAFETY

ADDITIONAL FEATURES

- 1 **Co-moulded rubber casing**
offers high shock-absorbing capacity and increased levels of grip.
- 2 **Easy-slide thumb lock**
- 3 **Tough steel easy-read tape blade**
Double sided option available.
- 4 **Corrosion-resistant end hook**
to increase longevity.
- 5 **Tape information**
for easy product identification.



ACCESSORIES



TS-3022SLC



LE-2080B & LE-2080NV



LE-2270 & LE-2271

FIRST FOR QUALITY

ORDERING INFORMATION

PART NO	TAPE TYPE	FULL LENGTH	BLADE WIDTH	WEIGHT
LM-1651RD	Single Sided	5m	25mm	260g
LM-1645R	Double Sided	5m	25mm	260g

SUITABLE INDUSTRIES



SCAFFOLDING



OIL & GAS



CONSTRUCTION



ROOFING



BRICKWORK



DEMOLITION



TRANSPORTATION



MAINTENANCE

FIRST FOR SOLUTIONS

01432 346800 | sales@leachs.com | www.leachs.com