

PRODUCT DATA SHEET 09.23



39021

LADDER TAG INSERT

DEFINING **FEATURES**

- Versatile polypropylene
- Easy to read layout
- Dry wipe
- Waterproof

CONFORMITY:

In accordance with BS EN131.



Ref No. Ladder to be used for (tick 1): Professional use Non-professional use Inspection Period INSPECTION PERIOD NOT INSPECTION	LADDER INSPECTION CHECKLIST PRE-USE CHECKS Look for any wear, decay, dents, cracks, splits or warping Look for any loose or missing rungs End of the stiles to be sound and in good Metal ties rods to be in place under rungs Ladders must be a
Next Inspection Due: Date Signature	grease, dirt and any other contaminant Wooden ladders should not be painted Wooden ladders should not be painted All anti-slip feet to be in place and worn IN USE CHECKS Ladders to be on a sound base Ladders to be on a sound base adder to be at an angle of 75° ratio of the ladders for light duty, short duration than three points of contact with the TOVER REACH - Move the
	sr should be tied to prevent it sible to secure the ladder, person to foot the ladder ny material or equipment a ladder Provision must terials and / or carried in a tool belt or se a hoist line

FIRST FOR SAFETY

ORDERING INFORMATION

OFTEN PURCHASED WITH:



ORDERING INFORMATION

PART NO	PACK QUANTITY	MATERIAL	DIMENSIONS	MAX USE TEMPERATURE	APPLICATION
SC-3902I	12 Inserts	Polypropylene	164mm x 50mm	125 degrees	Ladder

SUITABLE INDUSTRIES

