

# ECHO BARRIER<sup>®</sup>

Environmentally Sound

## H8<sup>™</sup> Acoustic Barrier

### Specifications



World-leading  
temporary noise control.



01432 346800  
sales@leachs.com  
www.leachs.com

# ECHO BARRIER®


Environmentally Sound

## H8™ Acoustic Barrier


The Echo Barrier H8™ is a temporary portable acoustic barrier that has been designed to fit on one standard 3.5m (12ft) fence panel making it ideal to cover large areas quickly. It has a very good noise reduction and absorption. It is lightweight, durable and water, fire and temperature resistant.



NOISE REDUCTION



NOISE ABSORPTION




## H8™ Acoustic Barrier specifications

Max Noise Reduction (Lab Tested)*	37 dB
Max Noise Absorption (Lab Tested)*	89%
Height	2050 mm (6 ft 9 in)
Width	3650 mm (12 ft)
Weight	13 kg (28.6 lb)
Water resistant test standard*	BSEN 60529:1992 IPX6 / IPX9
Fire resistant test standard*	BS 7837-1996
Dust resistant test standard*	BSEN 60529-1992
Cold resistant test standard (result)*	BSEN 60068/2/1:2007 (-40 degrees)
UV resistant	3 years (USA + Canada), 5 years (rest of the world)
Safety features	Night-time reflective strips, hazard icons
Quick install	2 person in 30 seconds with installation kits, foldable
Installation kits	Yes
Anti-theft	Security cable, Data tag
Cleaning	Power wash
Identification code part number	Unique RFID number per unit
Manufacturer's warranty	1 year
Colour Options	On request

## Effective installation

Position barriers closer to the noise source for maximum acoustic shadow



## What makes our acoustic barriers so effective?



### Front outer layer

Extremely durable, waterproof, high quality PVC, with optimum mass to ensure maximum noise reduction whilst retaining a professional appearance.




### Acoustic absorbent

Lightweight acoustic foam prevents noise reflecting off the barrier.



### Waterproof breathable fabric

Multiple purpose breathable fabric allows noise to be absorbed while ensuring no water enters the barrier.



Patent protected, ©2017, Trade mark protected 2017



01432 346800  
 sales@leachs.com  
 www.leachs.com