7017 TEXTILE LAUNDRY TAG

- UHF Textile Laundry Tag, with more than 200 industrial washing cycle times, capable of 60 bar pressure, stable and reliable RF performace.
- Warranty 200 industrial washing cycle.
- With the narrowest size of 10mm.

Type: 10-Laundry7017

Assembly method: sewing (Thread installation)

ADVANTAGES:

- More than 200 wash cycles.
- Both material and design have been tested for reliability.
- **4** 100% function tested.

MAIN FEATURES:

- Can customize size for customers.
- Soft material.
- Smaller module inside the tag.
- Can stick under 60 bar pressure.

APPLICATIONS:

- Industrial washing.
- Management of uniforms.
- Medical apparel management.
- Military clothing management.
- Personnel patrol management.

CHARACTERISTICS:

| Compliance | EPC Class1 Gen2, ISO18000-6C |
|--------------|---|
| Frequency | 865~868MHz, or 902~928MHz |
| Chip | Impinj R6P |
| Memory | EPC 96bits,User 32bits |
| Read/write | Yes |
| Data Storage | 20 years |
| Lifetime | 200 wash cycles or 2 years from shipping date |
| | (whichever comes first) |
| Material | Textile |
| Dimension | LxWxH: 70 x 10 x 1.5mm / 2.756 x 0.398 x 0.059 inch |
| Storage | -40°C∼ +85 °C |
| Temperature | -40 C +63 C |
| Operating | 1) Washing: 90° C (194°F), 15 minutes, 200 cysle |
| Temperature | 2) Pre-drying in Tumbler: $180^{\circ}\mathrm{C}(320^{\circ}\mathrm{F})$, $30\mathrm{minutes}$ |
| | 3) Ironer: 180 $^{\circ}$ C (356 $^{\circ}$ F), 10 seconds, 200 cycles |
| | 4) Sterilization Process: 135 °C (275°F), 20 minutes |
| Mechanical | Up to 60 bars |
| Resistance | Op to 60 bars |
| Delivery | Single |
| format | Jiligic |
| Installation | Thread installation |
| Method | Thread Histaliation |
| Weight | ~ 0.6g |
| Package | Antistatic bag and carton |
| Color | White |
| Power Supply | Passive |
| Chemicals | Normal common chemicals in the washing processes |
| RoHS | Compatible |
| Read | Up to 5.5 meters (ERP=2W) |
| distance | Up to 2 meters (With ATID AT880 handheld reader) |
| Polarization | Liner |
| | |