7025 ON METAL TAG

A cost effective UHF Tag used on metal surfaces

It can work stably and reliably on metal surface and off metal surface, which is widely used in indoor and outdoor asset management.

ADVANTAGES:

- Work stably on metal surface amd off metal surface
- 100% memory writing tested.
- Both material and design have been tested for reliability.
- 100% function tested by Voyantec Tagformace.


MAIN FEATURES:

- Can customize size for customers.
- Logo can be printed on the surface of tag.
- 🐇 🛛 Can be lasered with barcode
- Resistant to acid-base, waterproof
- Convenient for installation.

APPLICATIONS:

- 🐇 Storage management.
- IT equipment management.
- Metal containers management.
- Metal equipment management.
- Personnel patrol management.
- Fixed asset management.





CHARACTERISTICS :

Compliance	EPC Class1 Gen2; ISO18000-6C
Frequency	902-928MHz , 865~868MHz (Can
	customize frequency)
Chip	NXP Ucode 7M/8
Memory	EPC 96bits User 32bits/EPC 128bits User Obits
Read/write	Yes (EPC and User)
Data Storage	50 years
Warranty	One year
Material	ABS
Dimension	70mm L x 25mm W x 5mm H
Storage Temperature	-25 ℃ ~ +70 ℃
Operating Temperature	-40 ℃ ~ +70 ℃
Storage humidity	$5\% \sim 95\%$
Delivery format	Single
Installation Method	Screw, rivet, glue, or 3M300LSE tape
Weight	~ 5g
Package	Bubble bag and carton
Color	Grey
Power Supply	Passive
Drop Test	1 meters high, 200 drop test passed
Alcohol test	95% alcohol test passed
Gasoline test	Passed
High & low temperature	-40 ℃ ~ +70℃, 7 cycles, total 48 hours
shock test	
Temperature cycle test	-40°C~+70°C, 7 times cycle time testing,
	48 hours total
RoHS	Compatible
Read distance on metal	Up to 3 meters (EIRP=4W)
surface	Up to 1.5 meters (With ATID AT880 handheld
	reader)
RF performance	100% tested by Voyantic Tagformace
consistency test	
Options	pre-encoding, Barcode laser, logo