

STAR*TRIO LONG GUN COMBO LIGHT

WITH RAIL MOUNT AND REMOTE PRESSURE SWITCH


OPERATING MANUAL



Do not stare into beam



Fire, explosion, or burn hazard



Safety measures must be practiced at all times while handling a firearm







IMPORTANT WARNINGS CAUTION: The Star★Trio Long Gun Combo Light features a powerful beam that	*Runtime is defined as the amount of time between the initial switching of the flashlight and the decrease of brightness to 10% of the rated output on new
may cause the device to become uncomfortably warm when operated for an	batteries.
extended duration. The increased temperature does not present a burn hazard, and the device is safe to use in tactical situations, such as clearing rooms or	BATTERY INSTALLATION/REMOVAL
checking for intruders, for short periods of time.	Uses one 18650 battery or two CR123 batteries. Unscrew the tailcap and remove
FAULURE TO DEAD, AND FOLLOWITHESE OPERATING INSTRUCTIONS AND	depleted battery(s), insert fresh battery(s) positive end first, replace and tighten
FAILURE TO READ AND FOLLOW THESE OPERATING INSTRUCTIONS AND WARNINGS WHEN HANDLING A FIREARM OR THE STAR★TRIO LONG GUN	tailcap.
COMBO LIGHT CAN BE DANGEROUS AND CAN RESULT IN SERIOUS INJURY,	18650 USB BATTERY CHARGING
DAMAGE TO PROPERTY, OR DEATH.	The Star ★Trio Long Gun Combo Light may ship with an 18650 USB
 Use of a firearm under any circumstance may be dangerous. SERIOUS INJURY OR EVEN DEATH may result without proper training in the safe 	rechargeable lithium-ion battery with integrated charge port. The battery should be fully charged before its first use. To charge the 18650 USB battery,
handling of firearms. Proper training should be obtained from an	insert the micro-USB plug into the connector near the positive end of the
accredited firearms safety program conducted by competent, qualified	battery. The battery may be left plugged into a micro-USB cable continuously;
instructors in the military, police academies, or National Rifle Association-affiliated instruction programs.	there is no danger of overcharge.
Read your firearm's manual before attaching your gun-mounted light.	LED charge indicators
Never point a firearm at something you are not willing to destroy.	Red: charging
Thoroughly practice (employing safe training conditions) with the Star★ Trio Long Gun Combo Light and firearm before using the weapon in a	Blue: charged
tactical situation.	FLASHLIGHT MOUNTING/REMOVAL
	MAKE SURE THAT THE FIREARM IS UNLOADED AND THE BREECH IS OPEN. IT IS
BEFORE ATTACHING, INSPECTING, OR SERVICING A FIREARM-MOUNTED STAR★ TRIO LONG GUN COMBO LIGHT	IMPERATIVE THAT SAFETY MEASURES BE EMPLOYED AT ALL TIMES WHILE
Engage the safety on the firearm if applicable	HANDLING THE FIREARM. The Star★Trio Long Gun Combo Light is designed to be rapidly and securely
Remove the magazine from the firearm if applicable	attached to or detached from any MIL-STD-1913 (Picatinny) rail with only the
3. Open the action and inspect the chamber to be sure it is empty	use of a hex wrench. To mount the light onto a rail
IT IS IMPERATIVE THAT SAFETY MEASURES BE EMPLOYED AT ALL TIMES WHILE	 Use the hex wrench to unscrew the mount until the rail clamp is fully open and loose enough to place around the rail. NOTE: There is no need
HANDLING THE FIREARM.	to continue loosening the screw beyond this point, as it will eventually
BATTERY	fall off if rotated too many times. 2. Place the clamps around the rail at the preferred position.
WARNING: FIRE, EXPLOSION, BURN HAZARD	 Place the clamps around the rail at the preferred position. Check for fit and alignment, then tighten the clamp by rotating the
DO NOT: misuse, short-circuit, improperly store or discard, disassemble, or heat	screw back in the opposite direction until the light is securely attached
above 212°F (100°C). Keep away from children.	to the firearm.
USE ONLY: qualified 3.7V 18650 or 3V CR123A batteries.	To mount the remote pressure switch, either
This product is not designed to use rechargeable CR123 cells.	(1) place the mount retaining clips at the preferred position on the rail then
The Star★Trio Long Gun Combo Light will function effectively when installed	insert the remote pressure switch into the seat between the clips OR
with the Star * Tactical 18650 USB Rechargeable 3.7V Protected Lithium-ion	(2) apply the mounting adhesive to the bottom of the remote pressure switch
3500mAh Battery.	then attach the remote pressure switch to any suitable position on the firearm.
LED	VISIBLE LASER / INFRARED LASER SIGHTING
CAUTION: LED radiation (RG-2)	Windage: turn the windage screw to sight the visible laser/infrared laser right
Do not stare into beam. May be harmful to eyes.	(clockwise) or left (counterclockwise). Elevation: turn the elevation screw to sight the visible laser/infrared laser up
IEC 62471:2006	(clockwise) or down (counterclockwise).
LASER Class 3R lasers are safe when handled carefully.	GENERAL OPERATION Press the ON/OFF switch to toggle the Star★Trio Long Gun Combo Light on or
Do not look into the directed or reflected beam.	off.
Avoid accidental exposure to eyes.	
Do not aim at aircraft. Can cause eye injury up to 110 ft (34 m) away.	QUICK-SWITCH DIAL Turn the dial to point at the desired operation mode.
	and to point at the desired operation mode.
CONTENTS Start Trial and Cun Comba Light with MIL STD 1013 will mount	REMOTE PRESSURE SWITCH
 Star * Trio Long Gun Combo Light with MIL-STD-1913 rail mount Remote pressure switch with MIL-STD-1913 rail mount retaining clips 	Constant-on: press circular locking switch until click Momentary: press rectangular pressure switch
and mounting adhesive	
 18650 USB rechargeable 3.7V lithium-ion 3500mAh battery and charger 6-inch micro USB-A charging cable 	MAINTENANCE
b-inch micro USB-A charging cable hex wrench	Use a soft cloth and mild detergent to clean the glass lens and keep it free of dirt and grime.
	Note: Always avoid aggressive cleaning solutions.
SPECIFICATIONS 1,200 lumens	CONTACT
200m beam distance	Star * Tactical
IPX6 water resistance	www.startactical.com
 Machined aluminum alloy 192g/6.77oz (without battery) 	CONTACT@STARTACTICAL.COM
Multi-mode with quick-switch dial	
Runtime*	
Mode Hours	
LED 2.5	
Visible laser (L) 65 Infrared laser (IR) 100	
LED+L 2	
LED + IR 2.5	
LED + L + IR 2	