

Description	Curator Prime Coat is a hybrid undercoat-primer product with exceptional adhesion qualities. It is suitable for wood, both interior and exterior.
Recommended Uses	Suitable for use on wood, previously painted or glossy surfaces e.g. Interior /exterior doors, frames, windows and fences. Chemical resistance: NOT SUITABLE. Tannin resistance: NOT SUITABLE. NOTE: Stir thoroughly before use.
Colour Range Tint bases	Curator range white base colours White only
Solvent type Resin Type Finish VOC	Waterborne Acrylic <3% @60° EU limit for this product (Cat A/g): 30g/L (2010). This product contains max 30g/L VOC
Solids	58± 2% by weight 44± 2% by volume
Theoretical Coverage	Coverage per Litre: 10 m ² per coat depending on surface conditions & application techniques.
Recommended film thickness per coat	Wet: 90 micron Dry: 40 micron
Thinning	Product is ready for use, if thinning is required, use water only; one-part water to ten-part paint maximum.
Dry time	At ambient temperature (23 °C): Touch dry: 1-2 hours depending on film thickness and drying conditions. Re-coat after 4-6 hours. Full paint properties do not develop for a minimum of 7 to 10 days after application. NOTE: Do NOT apply if surfaces are in poor drying conditions. Do NOT apply in temperatures below 10°C or above 30 °C. Cool conditions, high humidity and heavy coats will lengthen drying times. Air ventilation will help improve drying conditions.
Storage	Store in dry, cool conditions and protect from frost.
Application method	Brush, roller or airless spray. Stir well before and during use. Apply by suitable brush, roller or spray.
Clean Up	Clean equipment with water immediately after use. Replace lid on can and stir thoroughly before re-use.
Surface Preparation	When painting previously painted wood or glossy surfaces which may contain silicone (household polishes etc) or if unsure of surface, degrease and rub down with appropriate sandpaper to help achieve a key. After sanding remove any residual dust with a water-dampened cloth to ensure surface is clean dry and sound before applying one coat of Curator PrimeCoat.
Safety, Health and Environmental Information	Avoid prolonged contact with skin and breathing of spray mist. A Safety Data Sheet is available on request.

IMPORTANT NOTE: The information contained in this Data Sheet is not intended to be conclusive, and any person using this product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from General Paints as to the suitability of this product for the intended purpose, does so at his or her own risk. Whilst we attempt to ensure that all advice we give about this product (whether in the sheet or otherwise) is correct, we have no control over the quality or condition of the substrate or the many factors affecting the use and application of this product. Therefore, unless we specifically agree in writing to do so, we do not accept liability whatsoever, or howsoever arising, for the performance of this product or from any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of this product. The information contained in this sheet is likely to change from time to time in the light of experience and our policy of on-going product updates.

HEALTH & SAFETY INFORMATION: This product should not be used without reference to the relevant Health and Safety Data Sheet, which General Paints Ltd. has provided for its customers. If for any reason a copy of this Data Sheet is not available, the user should contact General Paints Ltd. to obtain a copy before using this product.