

<b>Description</b>	A luxurious soft touch interior wall finish which exudes quality and opulence. This gorgeous smooth finish not only looks beautiful, but is also exceptionally hard-wearing, wipeable, great coverage and is resistant to many household stains. Enhanced matt is a low odour, low VOC acrylic emulsion with a depth of colour designed to last.
<b>Recommended Uses</b>	Suitable for use on domestic and light industrial walls and ceilings. Chemical resistance: NOT SUITABLE. Heat resistance: NOT SUITABLE – not suitable for use on radiators. NOTE: Stir thoroughly before use.
<b>Classification</b>	Curator Enhanced matt is classified as Class 1 Section 5.4 (wet scrub resistance) and Class 1 Section 5.5 (opacity) under EN13 300 / BS 13 300.
<b>Colour Range Tint bases</b>	Curator range consisting of 144 colours. White, Deep, Neutral
<b>Solvent type Resin Type Finish VOC</b>	Waterborne 100% Acrylic <3 % @60° European limit for this product (Cat A/a): 30g/L (2010). This product contains a max of 30g/L
<b>Solids</b>	52± 2% by weight, 36± 2% by volume
<b>Theoretical Coverage</b>	Coverage per litre : 10m <sup>2</sup> depending on surface conditions & application techniques.
<b>Recommended film thickness per coat</b>	Wet: 110 micron Dry: 40 micron
<b>Thinning</b>	Product is ready for use, if thinning is required, use water only; one-part water to ten part paint maximum.
<b>Dry time</b>	At ambient temperature (23°C): Touch dry: 2-4 hours depending on film thickness and drying conditions. Re-coat after 4-6 hours. Full paint properties do not develop for a minimum of 7 to 10 days after application. NOTE: Do NOT apply if surfaces are in poor drying conditions. Do NOT apply in temperatures below 10°C or above 30 °C. Cool conditions and high humidity will lengthen drying times. Air ventilation will help improve drying conditions.
<b>Storage</b>	Store in dry, cool conditions and protect from frost.
<b>Application method</b>	Brush, roller or airless spray. Stir well before and during use. Apply by suitable brush, roller or spray. For best results apply two coats. Some of the vibrant colours are low hide and may require additional coats. Ensure you use the correct colour undercoat as this may reduce the number of topcoats required. See your stockist for further advice. Very slight variation may occur between cans. When using more than one can make sure batch numbers are consistent and mix in a large container to ensure colour uniformity. Please note darker colours are prone to marking more easily than lighter colours.
<b>Clean Up</b>	Clean equipment with water immediately after use. Replace lid on can and stir thoroughly before re-use.
<b>Surface Preparation</b>	Ensure surface is sound, clean, dry and free from dirt and grease. Remove any loose or flaky paint. Surface defects (cracks, holes, etc) should be filled with a suitable interior grade filler or acrylic caulk. Fresh plaster, highly absorbent uncoated surfaces, highly porous prepainted surfaces or heavily filled surfaces should be primed with a high-quality wall primer followed by two neat coats of chosen colour.
<b>Cleaning Recommendations for Painted Surfaces</b>	Wash stain as soon as possible with a clean lint free cloth and clean soapy water. Rinse and allow to dry. Do not apply too much pressure as over enthusiastic scrubbing may damage the paint finish. Oil based stains may not be completely removed, marks from permanent markers will not be removed. Full paint properties do not develop for a minimum of 7 to 10 days after application (depending on drying conditions). The paint should not be washed before this time has elapsed.
<b>Safety, Health and Environmental Information</b>	Avoid prolonged contact with skin and breathing of spray mist. A Safety Data Sheet is available on request.

**IMPORTANT NOTE:** The information contained in this Data Sheet is not intended to be conclusive, and any person using this product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from General Paints as to the suitability of this product for the intended purpose, does so at his or her own risk. Whilst we attempt to ensure that all advice we give about this product (whether in the sheet or otherwise) is correct, we have no control over the quality or condition of the substrate or the many factors affecting the use and application of this product. Therefore, unless we specifically agree in writing to do so, we do not accept liability whatsoever, or howsoever arising, for the performance of this product or from any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of this product. The information contained in this sheet is likely to change from time to time in the light of experience and our policy of on-going product updates.

**HEALTH & SAFETY INFORMATION:** This product should not be used without reference to the relevant Health and Safety Data Sheet, which General Paints Ltd. has provided for its customers. If for any reason a copy of this Data Sheet is not available the user should contact General Paints Ltd. to obtain a copy before using this product.