



Product Specifications

VV465 Style Number

Construction Solid Polymer Core

Edge Profile Micro Bevel

7" wide, 48" long **Nominal Dimensions**

| Nominal Differencies | 7 Wide, 40 Tong | |
|---------------------------|-------------------------|--------------|
| | US Units | Metric Units |
| Actual Product Width | 7.13" | 18 cm |
| Actual Product Length | 48.03" | 122 cm |
| Wear Layer Thickness | 12 mil (0.012") | 0.3 mm |
| Overall Product Thickness | 0.173" | 4.4 mm |
| Core Thickness | 0.134" | 3.4 mm |
| Attached Underlayment | Attached Cork | |
| Attached Underlayment | 0.039" | 1 mm |
| Thickness | | |
| Finish | UV Acrylic | |
| Installation Methods | Floating or Direct Glue | |
| Profile | Angle/Tap | |
| Country of Origin | Imported | |
| | | |
| | | |



Packaging

Area per Box 28.52 sq ft 3 sq m Pieces per Box 12 pcs Weight per Box 41.89 lbs 19 kg **Boxes per Pallet** 45 boxes

Colors



Galaxy



The list of colors below complements the entire range of colors available for the current product. 2080 Magellanic Oak 2083 Centaurus Oak

Performance

Static Load (ASTM F970) **Passes** Residual Indentation (ASTM F1914) Passes Resistance to Heat (ASTM F1514) Passes Resistance to Light (ASTM F1515) **Passes** Passes Resistance to Chemicals (ASTM F925) Smoke Density (ASTM E662) Passes Radiant Panel (ASTM E648) Passes, Class I Slip Resistance (ASTM D2047) ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

30 Years

7 Year Light Commercial

Certifications

FloorScore Certified

GreenGuard (Certification, Gold, Private Label) Certified



