

Product Specifications

Style Number	VV489	
Construction	Solid Polymer Core	
Edge Profile	Enhanced Painted Bevel	
Nominal Dimensions	7" wide, 48" long	
	US Units	Metric Units

Actual Product Width	7.2"	18 cm
Actual Product Length	48.03"	122 cm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Overall Product Thickness	0.196"	5 mm
Core Thickness	0.157"	4 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.039"	1 mm
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	

Packaging

Area per Box	28.84 sq ft	3 sq m
Pieces per Box	12 pcs	
Weight per Box	48.5 lbs	21.99 kg
Boxes per Pallet	50 boxes	



2753 Trestle Pine

Colors



Performance

Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Smoke Density (ASTM E662)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.


COREtec Pro Plus HD 7"

Warranties

USF Lifetime


USF 15 Year Heavy Commercial

Coordinating Trim




Baby Threshold*

01V20 | 94"




T-Molding*

02V62 | 94"




Quarter Round

01V46 | 94"




Overlap Stairnose*

01V95 | 94"



Flush Stairnose

02V17 | 94"



Overlap Reducer

01V70 | 94"

*Packaged with molding track

Stair Tread



Stair Tread

03Z70 | 48"