

# TECHNICAL SPECIFICATIONS

# RTS TACTICAL XR32 NIJ CERTIFIED

LEVEL IV STANDALONE Thickness: 29 mm (1.1 in)

#### THREAT PERFORMANCE

Part Number	RTS-48210
5.56 x 45mm - MI93	6
Max Velocity 3150 ft/s (960 m,	/s)
7.62 x 39mm - M67	6
Max Velocity 2390 ft/s (728 m	n/s)
7.62 x 51mm - M80	6
Max Velocity 2800ft/s (853m/	/s)
5.56 x 45mm - M855/SS0109	6
Max Velocity 3150ft/s (960m/s	5)
7.62 x 39mm - M43 Max Velocity 2390t/s (728m/s	6

#### **Testing Protocol**

NIJ certification of hard armor requires submission of 10" x 12" test plates which must demonstrate the ability to defeat specific rounds tested to a valid NIJ shot pattern, after exposure to a stringent conditioning protocol to simulate aging and wear. Level III requires six M80 rounds per plate.

RTS Tactical Performance Fabrics holds itself to a higherstandard by publishing the minimum number of shots that each size plate can be expected to defeat under similar NIJ testing methods, as well as listing many additional threats not addressed under the NIJ certification process.

#### **General Information**

Ceramic/Spectra design. 1000 Denier CORDURA® fabric finish.

#### NIJ Standard-0101.06

Tested and verified to meet or exceed ballistic resistance as specified under NIJ Standard- 0101 .06 plus Special Rifle Threats validated.



A NIJ Certified Level IV Stand-Alone Shooter Cut Ceramic Plate, designed for superior protection against armor-piercing rounds. With its shooter cut design, advanced ceramic composite materials, rugged durability, and a 1000D Cordura cover for added resilience, the XR32 ensures unmatched ballistic performance without compromising mobility.

Designed to function as a stand-alone plate, this advanced ceramic armor eliminates the need for additional soft armor backing. Experience maximum mobility and comfort without compromising on protection for those who require agility in tactical situations.

### **Manufacturing Tolerances:**

Thickness dimensions are  $\pm$  3 mm (  $\pm$  1/8 in ). Width and length dimensions are  $\pm$  0.00 to -8 mm ( $\pm$ 0.00 to -0.3 in). All weights are  $\pm$  4 % .

## SHOOTER CUT - SINGLE CURVE - TORSO

0	Part Number	Width x Length	Weight
ď	RTS-48210	254 x 305 mm	3.2 kg
		(10.0 X 12.0 in)	(7.05 lb)

| ISO BA 9000 Body Armor Manufacturer | TIN 81-4183881 | DUNS Number 080432007

CACE 7D IAA

CAGE 7RJ44

7770 NW 22nd Ave, Miami, FL 33147, USA











