


FELCO 31 - Green

Pruning shear - Good performance - Anvil model Made in Switzerland by FELCO







> Reliable: comfortable, light, sturdy handles made of forged aluminium with a lifetime guarantee* / blade made of high-quality hardened steel and screw-mounted adjustable brass anvil / clean, precise cut / all parts can be replaced

> Efficient: easy cutting adjustment

> Ergonomic: hand protection is provided by the ideal shape of the handles / non-slip coating



RECOMMENDED FOR

Our recommendation (* Recommended,	🜟 🜟 = Strongly recommended, 🚖 🚖 🚖 = Best fit)
Viticulture	***
Arboriculture	***
Horticulture	***
Parks and Gardens	***
Nursery	***
Small hand	***
Average-sized hand	***
Large hand	***
Right-handed	***
Left-handed	***

THE POINTS OF EXCELLENCE



Forged aluminum handles

Lightweight, strong and sturdy thanks to special aluminum alloys and advanced precision forging methods. Equipment comes with a lifetime guarantee*.

ACCESSORIES








FELCO 980 Maintenance product Spray



FELCO 990 Maintenance product Grease



SPARE PARTS



FELCO	REF.	Designation	Composition	UCC Barcode
<u> </u>	30/3	Blade with washer	1x 30/3 + 1x 30/25	7 83929 40030 3
00	31/4	Anvil with screws	1x 31/4 + 1x 31/6 + 1x 31/7 + 2x 31/13	7 83929 40097 6
00=	30/90	Kit	1x 30/8 + 1x 30/9 + 1x 30/25	7 83929 40032 7
	30/91	Kit	2x 30/11	7 83929 40033 4
0 🐠 🤹	30/92	Kit	1x 2/13 + 1x 30/12 + 1x 2/14	7 83929 40034 1
01	30/1	Handle without blade	1x 30/1 + 4x 7/5B + 1x 7/10 + 1x 6/35	7 83929 40191 1
108 · 01	31/2	Handle without anvil	1x 31/2 + 1x 2/13 + 1x 30/12 + 1x 2/14 + 1x 7/36	7 83929 40200 0
\sim	6/35	Coating for blade handle	1x 6/35	7 83929 40219 2
5	7/36	Coating for anvil- blade / anvil handle	1x 7/36	7 ¹ 83929 40239 0



-	7/5B	Rivet for blade	1x 7/5B	7"83929"40240"6
-	31/6	Screw for anvil 6 mm	1x 31/6	7"83929"40352" 6
=	31/7	Screw for anvil 8 mm	1x 31/7	7 83929 40354 0
	30/8	Bolt	1x 30/8	7 ⁸ 83929 ⁴ 0198 ⁰ 0
O	30/9	Nut	1x 30/9	7 83929 40199 7
	7/10	Bush	1x 7/10	7 83929 40235 2
0	30/25	Washer	1x 30/25	7"83929"40195"9
0	31/13	Washer	1x 31/13	7 83929 40356 4
	30/11	White spring	1x 30/11	7"83929"40192"
	30/12	Thumb catch	1x 30/12	7 83929 40193 5
0	2/13	Spring for thumb catch	1x 2/13	7"83929"40154"6
2 20	2/14	Screw for thumb catch	1x 2/14	7"83929"40155"3



MAINTENANCE





Cleaning

It is advisable to clean your tool after each use.

If your tool is particularly dirty or subject to rusting after exposure to moisture, do not delay cleaning.

Oiling

After cleaning, it is advisable to oil the tool so as to protect it from corrosion. The oil will also unjam the tool.



Sharpening

It is advisable to sharpen your tool at least once a day, but if you feel that your tool is not cutting as well as usual, sharpen it right away!



Dismantling

It is advisable to dismantle your tool on a regular basis, but at the very latest when it appears to be jammed.



PARTS REPLACEMENT



Changing the blade

When the blade and the anvil-blade no longer cross, or when the blade is badly damaged, it is advisable to change it.

Regulate the working of the blade and anvil-blade by adjusting the tightening of the nut. The blade should rub against the anvil-blade over 2/3 of its length.



Changing the thumb catch

When the thumb catch is damaged and loosens when used, even when the screw is readjusted, change it.



Changing the plastic coatings for handles If the coatings are badly damaged, you can replace them.

Soak the coatings for 2 minutes in boiling water - recommended glue: Loctite 415.