DITEC MARINE PRODUCTS LLC SAFETY DATA SHEET



Section 1: Identification

Product Name: Ditec Marine Wipeout	Product Code: H006987
Ditec Marine Products, LLC	-
W229 N2512 Duplainville Road	E
Waukesha, WI 53186	C
USA Tel: 1 800 572 4390	С

Emergency Phone:

CHEMTREC: Canada and USA - (800) 424-9300 CHEMTREC: In Mexico - 01-800-681-9531

Product Use: Cleaning / Washing Agent Not recommended for: NA

Section 2: Hazard(s) Identification		
GHS Ratings:		
Flammable liquid	4	Flash point >= 60°C (140°F) and <= 93°C (200°F)
Skin corrosion/irritation	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Serious eye damage/eye irritation	2A	Eye irritant: Subcategory 2A, Reversible in 21 days

GHS Hazards

H227	Combustible liquid
H315	Causes skin irritation
H319	Causes serious eye irritation

GHS Precautions

P210	Keep away from heat/sparks/open
	flames/hot surfaces – No smoking
P235	Keep cool
P264	Wash face, hands, and any exposed
	skin thoroughly after handling
P280	Wear protective gloves/protective
	clothing/eye protection/face protection
P321	Specific treatment (see first aid
	treatment on SDS)
P362	/
1 002	Take off contaminated clothing and wash before reuse
	wash before reuse
P302+P352	If on skin: Wash with plenty of soap and
	water.
P305+P351+P338	If in eyes: Rinse cautiously with water
	for several minutes. Remove contact
	lenses, if present and easy to do.
	Continue rinsing.
P332+P313	If skin irritation occurs: Get medical
	advice / attention
P337+P313	If eye irritation persists get medical
	advice / attention
P370+P378	In case of fire: Use for extinction
P403+P235	•••••••
F4037F233	Store in a well ventilated place. Keep
	cool

Warning



Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Water 7732-18-5 90% - 100%			
2-Butoxyethanol 111-76-2 5% - 10%	50 ppm TWA; 240 mg/m3 TWA	20 ppm TWA	NIOSH: 5 ppm TWA; 24 mg/m3 TWA
Isopropyl alcohol 67-63-0 1% - 5% Vapor Pressure: 31.503 mmHg	400 ppm TWA; 980 mg/m3 TWA	400 ppm STEL 200 ppm TWA	NIOSH: 400 ppm TWA; 980 mg/m3 TWA 500 ppm STEL; 1225 mg/m3 STEL

Section 4: First-aid Measures

Inhalation

Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

Eye Contact

Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly.

Skin Contact

Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash clothing separately and clean shoes before reuse.

Ingestion

If swallowed, do NOT induce vomiting. Give victim a glass of water. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Section 5: Fire-fighting Measures

Extinguishing Media

Use media suitable for the surrounding fire.

Specific Hazards Arising from the Chemical None known.

Special Protective Equipment and Precautions for Firefighters

SDS for: 1.H006987.TTVNNR.std.2

Section 6: Accidental Release Measures

Spill and Leak Procedures

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations

Section 7: Handling and Storage

Handling Procedures

Use with adequate ventilation. Avoid breathing dusts, mists, and vapors. Do not get in eyes, on skin, or on clothing. Wear eye protection and protective clothing. Wash thoroughly after handling.

Storage Requirements

Store containers in a cool, dry, well ventilated place. Keep container closed when not in use.

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Water			
7732-18-5			
2-Butoxyethanol 111-76-2	50 ppm TWA; 240 mg/m3 TWA	20 ppm TWA	NIOSH: 5 ppm TWA; 24 mg/m3 TWA
Isopropyl alcohol 67-63-0	400 ppm TWA; 980 mg/m3 TWA	400 ppm STEL 200 ppm TWA	NIOSH: 400 ppm TWA; 980 mg/m3 TWA 500 ppm STEL; 1225 mg/m3 STEL

ENGINEERING CONTROLS: Provide ventilation sufficient to maintain exposure below the recommended limits.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant the use of a respirator.

SKIN PROTECTION: Wear impervious protective gloves. Wear protective gear as needed - apron, suit, boots.

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

HYGENIC PRACTICES: Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

Section 9: Physical and Chemical Properties

Odor: Not Available	Appearance: Clear Colorless Liquid
Odor threshold: Not Available	Vapor Pressure: Not Available
pH: Not Available	Vapor Density: Not Available
Melting point: Not Available	Density: Not Available
Solubility: Not Available	Freezing point: Not Available
Flash point: Not Available	Boiling range: Not Available
Flammability: Not Available	Evaporation rate: Not Available
Specific Gravity: 0.998	Explosive Limits: Not Available

Viscosity: Not Available

Decomposition temperature: Not Available

Grams VOC less water: Not Available

Section 10: Stability and Reactivity

Chemical Stability:

STABLE

Incompatible Materials None known.

Conditions to Avoid None known.

Hazardous Decomposition Products None known.

Hazardous Polymerization

Hazardous polymerization will not occur.

Section 11: Toxicology In	formation		
-	.D50: 1,941mg/kg y LC50: 2,561mg/L		
Component Toxicity 111-76-2	2-Butoxyethanol Oral LD50: 470 mg/kg (Rat) Dermal LD50: 99 mg/kg (Rabbit) Inhalation LC50: 450 ppm (Rat)		
67-63-0	Isopropyl alcohol Oral LD50: 1,870 mg/kg (Rat) Dermal LD50: 4,059 mg/kg (Rabbit)		
Routes of Entry: Inhalation Ingestion Skin contact Eye contact			
Target Organs Blood Eyes	Kidneys Liver	Central Nervous System	Skin Respiratory System
Effects of Overexpos	Sure		
<u>CAS Number</u> None	Description	<u>% Weight</u>	<u>Carcinogen Rating</u> N/A
Section 12: Ecological Inf	formation		

Component Ecotoxicity

Section 13: Disposal Considerations

Dispose of in accordance with local, state and federal regulations.

Section 14: Transportation Information

The following is for US DOT Highway Transportation. Other modes/jurisdictions may have different classifications.

Non-Regulated.

Section 15: Regulatory Information

CERCLA/SARA Hazardous Substances

DEA List I and II Chemicals

OSHA Process Safety Management Highly Hazardous Chemicals

U.S. Clean Air Act Toxic and Flammable Substances

SARA 313

This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know-Act of 1986 (40 CFR 372):

67-63-0 Isopropyl alcohol 1 - 5%

This information must be included in all SDSs that are copied and distributed for this material.

TSCA 8(b) Inventory

67-63-0 Isopropyl alcohol 111-76-2 2-Butoxyethanol 7732-18-5 Water

Country

Regulation

All Components Listed

Section 16: Other Information

Disclaimer

The information herein is believed to be correct, but does not claim to be all inclusive and should be used only as a guide. Neither the above named supplier nor any of its affiliates or subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All chemical reagents must be handled with the recognition that their chemical, physiological, toxicological, and hazardous properties have not been fully investigated or determined. All chemical reagents should be handled only by individuals who are familiar with their potential hazards and who have been fully trained in proper safety, laboratory, and chemical handling procedures . Although certain hazards are described herein, we can not guarantee that these are the only hazards which exist. Our SDS are based only on data available at the time of shipping and are subject to change without notice as new information is obtained. Avoid long storage periods since the product is subject to degradation with age and may become more dangerous or hazardous. It is the responsibility of the user to request updated SDS for products that are stored for extended periods. Disposal of unused product must be undertaken by qualified personnel who are knowledgeable in all applicable regulations and follow all pertinent safety precautions including the use of appropriate protective equipment (e.g. protective goggles, protective clothing, breathing equipment, face mask, fume hood). For proper handling and disposal, always comply with federal, state and local regulations.

STATEMENT OF COMPLIANCE

Wipeout

Wipeout is readily biodegradable and is comprised of environmentally responsible raw materials and non-hazardous chemicals. Its components meet or exceed the highest global environmental regulatory requirements and are fully compliant with the standards of MARPOL Annex III and MARPOL Annex V. Wipeout is free from harsh and harmful chemical ingredients, making it safe to discharge into water at both full concentrate or with wash water without harming the marine environment. This product is NOT a marine pollutant.