




Harland Sharp™

Custom Speed Parts Mfg., Inc.
 19769 Progress Drive • Strongsville Ohio 44149
 Ph: (440) 238-3260 • Fax: (440) 238-2204
www.harlandsharp.com

Part # S605k

This high quality rocker kit includes heavy wall, specially hardened rocker shafts, needle bearing roller rockers with adjusters & 12pt. jam nuts, billet steel hold downs and spacers. For ease of installation we included a diagram of the rocker assembly with proper placement of the components.




Replacement Parts:

- 8 pcs. - L605-1 rocker arms (*specify ratio*)
- 8 pcs. - R605-1 rocker arms (*specify ratio*)
- 2 - Shafts
- 2 - SP-2030 spacers
- 2 - SP-1540 spacers
- 2 - SP-0235 spacers
- 8 - Hold Downs
- 4 - Snaprings
- 16 - Adjusters & Nuts

HS also recommends the following installation tips.

- Oil adjusters and install into rockers before bolting to engine. Leave adjusters loose.
- Apply oil or lube to roller tip and pushrod cup before installing on engine or allow rocker assembly to soak in 30W oil for 1/2 hour prior to install.
- You want approximately .008 to .010 clearance gap 1 place bolt to bolt
- Torque rocker hold down bolts to 25 ft. lbs.
DO NOT OVERTIGHTEN!
- Hand tighten adjuster jam nut or do not exceed 18-20 ft. lbs.
DO NOT OVERTIGHTEN!



The rocker adjusters are a 7/16-20 screw with a 5/16 cup. You have to use pushrods with a 5/16 ball end. When setting pushrod length have no more than 3 and no less than 2 threads showing on the bottom side of the rocker, between the rocker body. This is for proper oiling and correct geometry.

If you need assistance with this please contact our tech support @ 440.238.3260 M-F 7am to 4pm EST. Thanks