



Dual-band Wi-Fi AC1200 Extender

DH-5201

Boost your Wi-Fi strength and expand your network coverage with the Prolink DH-5201 Dual-band Wi-Fi AC1200 Extender, helping your devices stay connected anywhere your network reaches. Functions as a repeater by default or switch to an Access Point base on your needs. Other user-friendly features include an additional ethernet port, smart LED indicator, and easy pairing device.



Key Features



Dual-concurrent

Extend to both 2.4GHz and 5GHz networks simultaneously, depending on the user usage and activity. Best suited for when high quality or availability of Wi-Fi is required.



1200Mbps High-speed Wireless

High Speed mode optimizes overall performance by combining the bandwidth of both the 5GHz and 2.4GHz channels to create a super quick and stable connection.



Smart LED Indicator

Locate the best position to place your extender to achieve an optimal Wi-Fi signal and connection.



Easy Device Pairing

Tap and hold on the WPS button located at the front of the device and the user's main router to sync it up with both devices.



Ethernet Port

Repeater mode provides additional Internet access for your wired devices while AP mode instantly turns your wired devices connection to a dual band wireless access point when Ethernet cable is plugged in.



Easy Setup

3-step installation
Step 1: Login Password Creation
Step 2: Network Selection
Step 3: Enter Network Password

Specifications

Hardware	Interface	1 x 10/100Mbps Ethernet Port (RJ45)
	Button	1 x WPS button, 1 x Reset Button
	LED	1 x Signal 1 x WPS 1 x Power
	Power Consumption	Up to 5.2W
	Power Option	Direct wall-plug
	Rated Voltage/Frequency	Input: 100 - 240 V , 50/60Hz
Wireless	Frequency Band	11n : 2.412 - 2.472GHz 11ac: 5.15GHz - 5.25GHz; 5.25GHz - 5.35GHz; 5.725GHz - 5.825Ghz
	Coverage ¹	Up to 200 sq meter (indoor)
	Standards	IEEE 802.11a/b/g/n/ac wave2
	Link Rate	11b: Up to 11Mbps (dynamic) 11g: Up to 54Mbps (dynamic) 11n: Up to 300Mbps (dynamic) 11ac: Up to 867Mbps (dynamic)
	Transmit Power	Up to 17dBm
	Antenna	2 x External 3 dBi Antenna
Software	Security	WPA-PSK/WPA2-PSK
	Internet (WAN) Connection Type	Repeater mode, AP mode
Environmental	Device Management	Web Browser / Mobile UI Domain Login Hide SSID Blocklist
	Operating Temperature	0°C ~ 40°C
	Storage Temperature	-40°C to 70°C
	Relative Humidity (Operational)	10% ~ 90%, non-condensing
Product Dimensions	Relative Humidity (Storage)	5% ~ 90%, non-condensing
	Dimensions (L x W x H)	80mm x 77mm x 79mm (UK) 80mm x 77mm x 89mm (EU)
Packaging Box Contents	Weight	180g (UK) 175g (EU)
		1 x DH-5201 1 x Quick Installation Guide

¹ Actual wireless performance and coverage may subject to environmental condition, application usage, and local regulatory requirement.

Product specifications are subject to change without further notice

Ver1.1_03.12.2021

Authorised Distributor/ Reseller:

Compatible with:



Windows



Mac OS



Linux