

Smart LED Bulb

DS-3606





Remote Control



Tunable White Control



Hub-fre



Control



Scenario
Customization



Smart Timer



Light Grouping



Enjoy the full spectrum of everyday light with your **DS-3606 Smart LED Bulb**. A simple touch or voice command is all you need to create the perfect home ambience, adjust lighting colour or brightness, and even schedule it to your sleep/wake schedule.

Key Features

16 Million Colours Design and customize endless lighting possibilities with 16 million colours to choose from.

Tunable White ControlTune the appearance from a cozy soft White (2700k) to an energetic bright White (6500k).

Hub-freeNo hub or extra equipment required. All you need is the mEzee app and Wi-Fi connection

to start controlling your bulb anytime, anywhere.

Voice ControlA quick and simple voice command is all it takes to turn on, off or dim your lightings with

Alexa Amazon or Google Assistant.

Remote ControlDouble-up your phone as a remote controller with the mEzee app. Works perfectly with

Android & iOS smart devices.

Scenario Customization Movie nights or cozy family gathering settings, you can adjust and match your mood or

activity accordingly.

Smart Timer Schedule your smart bulb to turn on and off at preset timings with preferred light settings

to go along with your daily routines.

Light Group ControlThese bulbs can be controlled individually or as a group, letting you set the ideal mood for

your lifestyle and preferences. Save your settings as different scenes for instant access.









Specifications

Driver Specification		
Form Factor	E14	
Input Voltage/Frequency (V/HZ)	AC220-240V 50/60Hz	
Input Power (W)	5W± 10%	
Input Current (A)	0.05A max	
PF	>0.5	
Output Current (mA)	220mA ± 5%	
Output No-load Voltage (V)	19VDC max	
Rated Voltage (V)	16VDC	
Efficiency (%)	≥75 (230V/50Hz)	
Standby Power (W)	<1	
Surge Protection	up to 1.5KV	
Operating Temperature (°C)	-10-40°C	
Storage Temperature (°C)	-20-70℃	
Certification	CE	

Product Optoelectronic Technical Specification

Lumen (LM)	400LM	
Colour Temperature (K)	2700K-6500K	
Colour Rendering Image	≥80	
Coverage Angle (°)	200°	
LED Specification	2700K 2835 9V 100mA	
	6500K 2835 9V 100mA	
	RGB 3030 150mA	
Lifetime	25000 hrs	
Function	CCT, Dimming, RGB	
Colour	16 million colour	
Wireless Standard	IEEE 802.11b/g/n	

Product Specifications may change without prior notice.

Authorised Distributor/ Reseller:

Ver1.0_23.09.2022





