

Wired Multimedia Desktop Combo

GMK-1003M

The **GMK-1003M Multimedia Desktop Combo** is the perfect duo that delivers all the comfort and functionality needed for a high volume day-to-day usage. Equipped with an adjustable stand to prop your keyboard up and an ambidextrous mouse design, this combo leaves nobody out when it comes to usability.









10-key number pad



Caps lock indicator light



Number lock indicator light



Optical tracking




Scroll wheel

Key Features



Multimedia keys

12 full multimedia shortcuts to let you immediately access common applications and boost efficiency in your workflow.



Adjustable keyboard stand

Prop up the keyboard with the built-in stands to your preferred typing posture for less strain and a more productive typing session.



Spill-resistant

Enforced protection against accidental spills to ensure prolonged usage and peace of mind while you work or play.



Plug and play

Plug your keyboard into a USB port, and it's all ready to go - no installation or extra fuss required.



Ambidextrous design

Contoured and symmetrical architecture that is specially crafted to suit both left and right-handed users.



Adjustable DPI button

Switch between 1000, 1600, or 2000dpi anytime for precise and accurate tracking that best fits your needs.



Specifications

KEYBOARD

Keys	104 (12 multimedia shortcuts)			
Key Switch	Rubber dome membrane			
Cable Length	1.4m			
Connection Mode	USB Type-A			
System Requirements	Windows 7/8/10/11 or later			
Dimensions (L x W x H)	439mm x 142mm x 23.7mm			
Weight	430g ± 10g			
Operating Humidity	20% ~ 90% RH			
Operating Temperature	0°C ~ 50°C			
Multimedia Functions	Л Media Player	Decrease Volume▶► Next	Increase Volume►/II Play/Pause	■ Stop
	A Home		My Computer	★ Favorites
MOUSE				
Buttons	4			
Hand orientation	Ambidextrous			
DPI	1000/1600/2000dpi			
Cable Length	1.5m			
System Requirements	Windows 7/8/10/11 or later			
Dimension (L x W x H)	115mm x 65.8mm x 33.3mm			
Weight	78g ± 10g			
Operating Humidity	0% ~ 90% RH			
1 3 /	0% ~ 90% RH			
Operating Temperature	0% ~ 90% RH 20°C ~ 80°C			

Ver1.0_10.04.2023

