



2-port GaN PD Charger IntelliSense

GT-23301



GaN Technology



Worldwide Input Voltage



Deliver up to 33W



IntelliSense Technology



Advanced Protection



4X Faster Charging



USB Type-C PD



PD 3.0 PPS



The **Prolink GT-23301 33W 2-port GaN PD Charger** with IntelliSense features GaN technology, delivering more charging power with much smaller physical size and weight than conventional charger. It comes with dual charging ports, letting users charge up to 2 devices simultaneously. Its IntelliSense feature helps to detect and automatically distributes the right amount of charging current for your connected devices, protecting them from over-voltage, over-current, over-temperature, overload and even short circuits.

Key Features

- GaN technology ensures a smaller and lighter charger with higher charging efficiency
- USB Type-C PD (Power Delivery) port offers rapid charging speed for all compatible USB-C devices
- Experience 4X faster charging speed with Qualcomm Quick Charge 3.0
- IntelliSense technology detects and automatically distributes the right amount of charging current for your connected device
- Deliver up to 33W total charging output
- Worldwide Input Voltage AC 100-240V 50/60Hz
- Advanced Protection (Over-voltage, over-current, over-temperature, overload and short circuit protection)
- Dual ports for simultaneous charging of up to 2 devices

Power Delivery 3.0 PPS & Quick Charge 3.0


Fast, safe & easy charging for your devices.



PD 3.0 PPS
USB-C: 33W Max

QC 3.0
USB-A: 18W Max


30 MINUTES CHARGE



PD 3.0 PPS



Conventional 5W Charger



QC 4+



Conventional 5W Charger

COMPATIBILITY



MacBook Air 13"



Tablet



Phone



Camera



Headset



Handheld Gaming Device






Wireless Earbuds



Apple Watch

* USB-C to Lightning Cable is required to fast charge a compatible iPhone or iPad.

Specifications

| | | |
|------------------------------|--|--|
| MODEL / PRODUCT NAME | GT-23301 2-port GaN PD Charger | |
| Dimension (L x W x H) | UK | 71.7 x 49 x 43.7mm |
| | US | 65.1 x 31.1 x 32.3mm |
| | EU | 78 x 35.5 x 32mm |
| Weight | UK | 65g |
| | US | 56g |
| | EU | 60g |
| Input | AC 100–240V 50/60Hz 0.8A | |
| Output | USB Type–C PD3.0 | 3.3–11V/3A, 3.3–16V/2A, 5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/1.5A (33W max) |
| | USB Type–A Quick Charge 3.0 | 3.6–6.5V/3A, 6.5–9V/2A, 9–12V/1.5A (18W max) |
| Charging Protocol | USB Type–C PD3.0 | PPS, PD3.0 & PD2.0, QC3.0 & QC2.0, Apple 2.4A, BC1.2, Samsung 2A & AFC, Huawei FCP |
| | USB Type–A Quick Charge 3.0 | QC 3.0 & QC 2.0, Apple 2.4A, BC1.2, Samsung 2A & AFC, Huawei FCP |
| Advanced Protection | Over-Voltage Protection | ✓ |
| | Short Circuit Protection | ✓ |
| | Over Temperature Protection | ✓ |
| | Overload Protection | ✓ |
| | Over Current Protection | ✓ |
| Package Contents | <ul style="list-style-type: none"> • 1 x GT-23301 2-port GaN PD Charger (EU/UK/US pin) • 1 x User Guide | |
| Available Plug Type | EU UK US    | |

Product specifications are subject to change without further notice

Ver1.1_22.09.2022

Authorised Distributor/ Reseller:



Register online for your Product Warranty at www.prolink2u.com



Certified by
ISO 9001



Singapore