

PTC26001

2-Port USB Wall Charger IntelliSense



The PROLiNK® PTC26001 2-Port USB Wall Charger comes with dual charging ports, letting users charge up to 2 devices simultaneously at a combined charging output of 60W. The wall charger includes a USB Type-C port which supports Power Delivery (PD) capable of providing optimized rapid charging for all compatible USB-C devices. It also comes with a Quick Charge 3.0 port provides up to 4X faster-charging speed than conventional charger. Its IntelliSense feature helps to detect and automatically distributes the right amount of charging current for your connected devices also fully protected from over-voltage, over-current, over-temperature, overload and even short circuits.

- Dual ports for simultaneous charging of up to 2 devices
- Experience 4X faster charging speed with Qualcomm Quick Charge 3.0
- USB Type-C PD (Power Delivery) port offers rapid charging speed for all compatible USB-C devices
- IntelliSense technology detects and automatically distributes the right amount of charging current for your connected device
- Deliver up to 60W total charging output
- Worldwide Input Voltage AC 100-240V 50/60Hz
- Fixed US plug with removable EU and UK plugs, ideal for frequent travelers
- Advanced Protection (Over-voltage, over-current, overload and short circuit protection)

Power Delivery 3.0

Charge compatible product from 0-50% after 30 minutes.

Up to
60W
Max



After charging for 30 minutes



USB-C with PD



Conventional Charging

Qualcomm QC3.0

Charge compatible product 4X faster than conventional charging technology.

Up to
18W
Max



After charging for 30 minutes



QC3.0



QC2.0



Conventional Charging

Model	IntelliSense Port				Input	Total Output
	Total No. of Ports	USB-C PD3.0	USB-C	USB-A QC3.0		
PTC26001	2	1	-	1	-	100-240V 50/60Hz 60W
PTC24501	2	1	-	1	-	100-240V 50/60Hz 45W
PTC23301	2	-	1	1	-	100-240V 50/60Hz 33W
PTC32501	3	-	-	1	2	100-240V 50/60Hz 30W

Also available: USB Desktop Chargers, Car Chargers and Wireless Chargers



PRODUCT LIABILITY INSURANCE

Insured by Singapore's NTUC Income Insurance Co-operative Ltd ("Insurer"), with a worldwide coverage (excluding the United States and Canada), and a product liability coverage of up to SG\$1,000,000

- Fida International (S) Pte Ltd shall submit all claims to the Insurer for assessment on the merits of the case
- Claimant will be notified by Fida International (S) Pte Ltd and/or the Insurer on the success of the claim in due course

Specifications

MODEL / PRODUCT NAME	PTC26001	
Dimension	70.5mm * 31mm * 69mm	
Weight	187g	
Input	AC 100V-240V 50/60Hz 1.5A	
Output 1 & 2	USB Type A Quick Charge 3.0	3.6V-6.5V / 3A, 6.5V-9V / 2A, 9V-12V / 1.5A [18W Max]
	USB Type C PD	5V / 3A, 9V / 3A, 12V / 3A, 15V / 3A, 20V / 3A [60W Max]
Advanced Protection	Over-Voltage Protection	✓
	Short Circuit Protection	✓
	Overload Protection	✓
	Over Current Protection	✓
Package Contents	<ul style="list-style-type: none"> • USB Wall Charger (US 2-Pin) • EU 2-pin Plug • UK 3-pin Plug • User Manual 	

Product specifications are subject to change without further notice

Certifications:
International Safety
(Electrical) Standards

IECEE CB Scheme:
IEC 60950



Ver1.0_12.9.2019

Authorised Distributor/ Reseller:

