

4-port GaN PD Charger IntelliSense

PTC412001



GaN Technology



PD 3.0



to 120W



technology



Advanced **Protection**



4X faster charging

USB Type-C PD



Worldwide Input Voltage




The Prolink PTC412001 120W 4-port GaN PD Charger with IntelliSense features GaN technology, this is to replace traditional Silicone components in a normal charger for better thermal and power efficiency, and gets your smart devices charged 3x faster with half the physical size and weight of a typical charger. It comes with 4 charging ports, allowing users to charge simultaneously at a total charging output of 120W. Also, its IntelliSense feature helps to detect and automatically distributes the right amount of charging current for your connected devices also fully protected from over-voltage, over-current, over-temperature, overload and even short circuits.

Key Features

- GaN technology ensures a smaller and lighter charger with higher charging efficiency
- USB Type-C PD (Power Delivery) USB Type-A (QC3.0) ports offer rapid charging speed for all compatible USB-C & USB-A devices
- Experience 3X faster charging speed with GaN Technology compare to typical charger
- IntelliSense technology detects and automatically distributes the right amount of charging current for your connected devices
- Deliver up to 120W total charging output
- Worldwide Input Voltage AC 100-240V 50/60Hz
- Advanced Protection (Over-voltage, over-current, over-temperature, overload and short circuit protection)
- Charge multiple USB devices simultaneously

Power Delivery 3.0 PPS & Quick Charge 4+

Fast, safe & easy charging for your devices.







Specifications

DEL / PRODUCT NAME	PTC412001 4-Port GaN PD Charger with IntelliSense	
Dimension (L x W x H)	77 x 30 x 61mm	
Weight	200g	
Input	AC 100-240V 50/60Hz 1.8A	
Output	Single Port	USB-C1/C2: 3.3V-21V/5A, 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A (100W max)
		USB-C3: 3.3V-21V/3A, 5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/1.5A (30W max)
		USB-A: 4.5V/5A, 5V/4.5A, 5V/3A, 9V/3A, 12V/2.5A 20V/1.5A (30W max)
	Two Ports	C1 + C2: 90W + 30W = 120W
		C3 + A: 5V/3A (15W max)
	Three Ports	C1 + C2 + C3: 65W + 30W + 18W = 113W
	Four Ports	C1 + C2 + C3 + A: 65W + 30W + 15W = 110W
Charging Protocol	USB Type-C PD3.0 & QC 4+	PD2.0, PD3.0, PPS, QC4, QC4+, QC2.0, QC3.0, Apple 2.4A, BC1.2, Samsung 2.0A, Samsung AFC, FCP, SCP, PE2.0, PE1.1
	USB Type-A Quick Charge 3.0	QC2.0, QC3.0, Samsung 2.0A, Apple 2.4A, DCP 1.5A, Samsung AFC, FCP, SCP, PE2.0, PE1.1
Advanced Protection	Over-Voltage Protection	✓
	Short Circuit Protection	✓
	Over Temperature Protection	✓
	Overload Protection	✓
	Over Current Protection	✓
Package Contents	 1 x PTC412001 4-port GaN PD Charger (Foldable US Pin) 1 x User Guide 1 x EU pin plug 1 x UK pin plug 	
Available Plug Type	EU UK US	

Product specifications are subject to change without further notice

Register online for your Product Warranty at www.prolink2u.com

