



2-Port PD Charger IntelliSense

PTC21801



Worldwide
Input Voltage



Deliver up
to 20W



IntelliSense
technology



Advanced
Protection



4X faster
charging



USB
Type-C PD



Dual
ports




The **Prolink PTC21801 20W 2-Port PD Charger with IntelliSense** comes with dual charging ports, letting users charge up to 2 devices simultaneously. The wall charger includes a USB Type-C port which supports Power Delivery (PD) capable of providing optimized rapid charging for all compatible USB-C devices. It also comes with a Quick Charge 3.0 port provides up to 4X faster-charging speed than conventional charger. Its IntelliSense feature helps to detect and automatically distributes the right amount of charging current for your connected devices also fully protected from over-voltage, over-current, over-temperature, overload and even short circuits.

Key Features

- **Dual ports for simultaneous charging of up to 2 devices**
- **Experience 4X faster charging speed with Qualcomm Quick Charge 3.0**
- **USB Type-C PD (Power Delivery) port offers rapid charging speed for all compatible USB-C devices**
- **IntelliSense technology detects and automatically distributes the right amount of charging current for your connected device**
- **Deliver up to 20W total charging output**
- **Worldwide Input Voltage AC 100-240V 50/60Hz**
- **Advanced Protection (Over-voltage, over-current, over-temperature, overload and short circuit protection)**

Power Delivery 3.0 & Quick Charge 3.0


Fast, safe & easy charging for your devices.



Power Delivery 3.0
5V/3A, 9V/2.2A, 12V/1.5A
(20W max)

Quick Charge 3.0
3.6-6.5V/3A, 6.5-9V/2A,
9-12V/1.5A (18W max)


30 MINUTES CHARGE



PD 3.0



Conventional
Charging



QC 3.0

Conventional
Charging

COMPATIBILITY



Tablet



Phone



Camera






Headset



Handheld
Gaming Device

* USB-C to Lightning Cable is required to fast charge a compatible iPhone or iPad.

Specifications

MODEL / PRODUCT NAME	PTC21801 2-Port PD Charger	
Dimension (L x W x H)	UK	74.8 x 49.7 x 39.2mm
	US	53.4 x 29.5 x 39.2mm
	EU	80.4 x 27 x 39.2mm
Weight	UK	65g
	US	55.5g
	EU	52.5g
Input	AC 100-240V 50/60Hz 0.6A	
Output	Single Port	USB-C: 5V/3A, 9V/2.2A, 12V/1.5A (20W max) USB-A: 3.6-6.5V/3A, 6.5-9V/2A, 9-12V/1.5A (18W max)
	Two Ports	C + A: 5V/3A
Charging Protocol	USB-C PD3.0	PD3.0 & PD2.0, QC3.0 & QC2.0, Apple 2.4A, BC1.2, Samsung AFC, Huawei FCP
	USB-A QC 3.0	QC 3.0 & QC 2.0, Samsung 2A & AFC, Apple 2.4A, BC1.2, Huawei FCP
Advanced Protection	Over-Voltage Protection	✓
	Short Circuit Protection	✓
	Over Temperature Protection	✓
	Overload Protection	✓
	Over Current Protection	✓
Package Contents	<ul style="list-style-type: none"> • 1 x PTC21801 2-Port PD Charger (EU/UK/US pin) • 1 x User Guide 	
Available Plug Type	EU  UK  US 	

Product specifications are subject to change without further notice

Ver1.1_17.12.2020

Authorised Distributor/ Reseller:



Register online for your Product Warranty at www.prolink2u.com



Certified by ISO 9001



Singapore