

CELEBRATE FALL RUNNER

Designed by Elise Lea for RK
www.robertkaufman.com

Featuring **Shades of the Season**



Finished project measures: 17-1/2" x 52"















Difficulty Rating: **Intermediate**

ROBERTKAUFMAN
F A B R I C S

For questions about this pattern, please email Patterns@RobertKaufman.com.

Fabric and Supplies Needed

Fabric amounts based on yardage that is 42" wide.

Color	Fabric	Name/SKU	Yardage	Color	Fabric	Name/SKU	Yardage
	A	SRKM-20902-14 NATURAL	5/8 yard		H	SRKM-20901-92 TERRACOTTA	1/8 yard
	B	SRKM-20938-15 IVORY	1/2 yard		I	SRKM-20899-16 BROWN	1/8 yard
	C	K001-1037 BONE	1/4 yard		J	SRKM-20938-133 GOLD	1/8 yard
	D	K001-1083 COFFEE	1/8 yard		K	SRKM-20901-7 GREEN	1/8 yard
	E	SRKM-20902-92 TERRACOTTA	1/8 yard		L	SRKM-20902-16 BROWN	1/8 yard
	F	SRKM-20902-7 GREEN	1/8 yard		M	SRKM-20898-322 ORANGE SPICE	1/8 yard
	G	SRKM-20898-191 AUTUMN	1/8 yard		Binding*	K001-1037 BONE	1/3 yard

**Also used for Fabric C*

Copyright 2022, Robert Kaufman
For individual use only - Not for resale

You will also need:
1-2/3 yards for backing

Notes Before You Begin

- Read through all of the instructions before beginning.
- All of the seam allowances are 1/4" unless otherwise noted.
- Press seam allowances open unless otherwise noted.
- Width of fabric (WOF) is equal to at least 42" wide.
- Right sides together has been abbreviated to RST.
- Remember to measure twice and cut once!

Cutting Instructions

From Fabric A, cut:

- one 12" x WOF strip. Subcut:
 - three 12" squares.
 - ◆ Cut two squares along both diagonals, creating eight side setting triangles. Note: two triangles will not be used.
 - ◆ Cut the remaining 12" square along one diagonal, creating two large corner setting triangles.
- one 6-5/8" strip. Subcut:
 - one 6-5/8" square.
 - ◆ Cut the square in half along one diagonal, creating two small corner setting triangles.

From Fabric B, cut:

- two 3-1/2" x WOF strips. Subcut:
 - sixteen 3-1/2" squares for the HSTs
- one 3" x WOF strip. Subcut:
 - eight 3" squares
- one 2-5/8" x WOF strip. Subcut:
 - sixteen 2-5/8" squares for the stem units. Mark a diagonal line on the back of each square.

From Fabric C, cut:

- five 1-1/4" x WOF strips. Subcut:
 - twenty-five 1-1/4" x 8" sashing strips

From Fabric D, cut:

- one 3" x WOF strip. Subcut:
 - eight 3" squares for the stem units

From Fabric E, cut:

- one 1-1/4" x WOF strip. Subcut:
 - eighteen 1-1/4" squares for the cornerstones

From each of Fabrics F-M, cut:

- one 3-1/2" x WOF strip. Subcut:
 - two 3-1/2" squares for the HSTs
 - Trim the remainder of the strip to 3" wide, then subcut:
 - ◆ three 3" squares

From the Binding, cut:

- four 2-1/2" x WOF strips.

Assemble the Half-Square Triangles (HSTs)

Step 1: Pair a 3-1/2" Fabric B square with a 3-1/2" Fabric F square, RST. Mark a diagonal line on the wrong side of one square. Sew 1/4" away from both sides of the marked line. Cut on the marked line, creating two half-square triangles (HSTs). Press toward the darker fabric. Trim to 3" square. Repeat to make four HSTs in this fabric pairing.




Step 2: Repeat Step 1 to make sets of four HSTs, each from Fabrics G-M paired with Fabric B.

Assemble the Stem Units

Step 3: Place a 2-5/8" Fabric B square in one corner of a 3" Fabric D square, right sides together. Sew along the diagonal, as shown. Trim the excess fabric, leaving a 1/4" seam allowance. Press toward the corner. Repeat on the opposite corner, with a second 2-5/8" Fabric B square. Make eight Stem Units.



Assemble the Blocks



Step 4: Gather:

- one 3" Fabric B square
- three 3" matching print squares
- four matching print HSTs
- one Fabric D Stem Unit

Arrange the units into three rows of three. Note the fabric placement and orientation in the Block Assembly Diagram.

Step 5: Sew the pieces together to form the rows. Press the seams in opposite directions every other row.

Step 6: Sew the rows together, nesting the seams and pressing the seams to one side to form the block. The resulting Block will measure 8" square.

Step 7: Repeat Steps 4-6 to make a total of eight Blocks.

Assemble the Runner



Step 8: Arrange the Blocks together in diagonal rows, as indicated in the Quilt Assembly Diagram. Sew each row together, using Fabric C sashing strips between each block and at the beginning and end of each row. Press seams toward the blocks. Make four block rows.

Step 9: Sew the side setting triangles to the ends of the rows, aligning the right angles together, as shown. The angled end will extend beyond the block. Press. Trim the excess from the points to be even with the block row, if desired.



Step 10: Gather cornerstone squares and sashing strips. Following the Quilt Assembly Diagram, sew each row together, using cornerstones between each sashing strip and at the beginning and end of each row. Press seams toward the sashing. Repeat to make five sashing rows.

Step 11: Sew the sashing and block rows together, pinning and nesting the seams. Press seams open or to the sashing.

Step 12: Sew the large corner setting triangles to each of the two remaining corners. Press. Sew the two small corner setting triangles to the rows indicated and press.

Step 13: Trim all four sides evenly, allowing a 1/4" seam allowance from the diagonal of each cornerstone, as shown.

Your table runner top is complete. Baste, quilt, bind and enjoy!

This pattern may be used for personal purposes only and may not be reproduced in any form without the express permission from Robert Kaufman Fabrics. This pattern is not for resale. All patterns, unless otherwise attributed, are © Robert Kaufman Co., Inc. 2005-2022. All rights reserved.