



25 Series 3590

IDROPULTRICI ALTA PRESSIONE
high pressure washers

OLIGHTPRO



3590



Caratteristiche Generali

- Pompa a 3 pistoni assiali comandati da piattello oscillante
- Pistoni in acciaio inox temprato
- Valvola di by-pass automatica con azzeramento della pressione nella testa della pompa
- Motore elettrico a induzione con protezione termica
- Pressostato di sicurezza per spegnimento della caldaia in caso di mancanza acqua
- Caldaia verticale, doppia serpentina e fondo in materiale refrattario
- Serbatoio gasolio 4 l
- Filtro acqua e filtro aspirazione gasolio
- Lunghezza cavo elettrico 5 m

General Features

- 3 Axial stainless steel pistons wobble-plate pump (2590, 3590) or with connecting rod system (4590)
- Tempered stainless steel pistons
- Automatic by-pass valve with pump head pressure discharge
- Single-phase induction electric motor with thermal protector
- With safety pressure switch to shut down the boiler in case of lack of water
- Vertical boiler with double heating coil and refractory compound base
- Fuel tank capacity 4 l
- Water filter and fuel inlet filter
- Electric cable length 5 m

3590

HRM

3590

WOBBLE PLATE

3590

BRASS

INDUCTION

MOD	COD	MAX bar	MAX psi	MAX l/h	MAX gph	MAX kW	MAX rpm	MAX Hz	MAX V	MAX kg NET
3590	24425	140	2050	480	127	2,4	2800	50	230~	52



°C Max Δ°t

90 55

90 55

90 45

Accessori standard Standard accessories

