

LED SPOTLIGHT-CANLESS REGRESSED MINI PANEL - CCT SELECTABLE UNIVERSAL VOLTAGE/DUAL DIMMING 3", 4", 5", 6"



CRI
80

COLOR SELECTABLE

2700K 3000K 3500K 4000K 5000K

WATTAGE
SELECTABLE

3 OPTIONS

HIGH
OUTPUT

DUAL
DIMMING
TRIAC
0-10V

WET
LOCATION
RATED

120-
277V

5
YEAR
WARRANTY

COMPATIBLE WITH:

LR35126
Emergency
LED Driver




COMPATIBLE WITH:
2" - LR22628, LR22637
3" - LR22630, LR22638
4" - LR22632, LR22640

LR35124
Emergency
LED Driver




COMPATIBLE WITH:
5" - LR22634, LR22642
6" - LR22636, LR22644

LR41002
New Construction
Mounting Plate



KNOCKOUTS
#0 #1 #2
KNOCKOUT SIZE
#0 Ø3.14" (Ø80 mm)
#1 Ø4.33" (Ø110 mm)
#2 Ø6.29" (Ø160 mm)

LR41006
New Construction
Mounting Plate



KNOCKOUTS
#0 #1 #2 #3 #4 #5
KNOCKOUT SIZE
#0 Ø2.12" (Ø54 mm)
#1 Ø3.15" (Ø80 mm)
#2 Ø3.75" (Ø95 mm)
#3 Ø4.25" (Ø108 mm)
#4 Ø5.25" (Ø132 mm)
#5 Ø6.25" (Ø159 mm)

LR41010
New Construction
Mounting Plate



KNOCKOUTS
#L0 #L1 #L2
KNOCKOUT SIZE
#L0 Ø2.12" (Ø54 mm)
#L1 Ø2.83" (Ø72 mm)
#L2 Ø3.75" (Ø95 mm)



KNOCKOUTS
#R0 #R1 #R2 #R3
KNOCKOUT SIZE
#R0 Ø3.25" (Ø82 mm)
#R1 Ø4.33" (Ø110 mm)
#R2 Ø5.25" (Ø132 mm)
#R3 Ø6.25" (Ø160 mm)

ELECTRICAL

ROUND		MODEL	DESCRIPTION	POWER	LUMEN	EFFICACY	INPUT VOLTS	DIMMABLE	FLOOD*	LIFETIME
	3"	LR22671	LED RMP3/2WO/5CCT/RD/WT/UNV/DD	9	750	80	120-277V	TRIAC/0-10V	90°	50,000
				12	1000					
	4"	LR22672	LED RMP4/3WO/5CCT/RD/WT/UNV/DD	12	1000	87	120-277V	TRIAC/0-10V	90°	50,000
				15	1400					
				19	1800					
	5"	LR22673	LED RMP5/3WO/5CCT/RD/WT/UNV/DD	16	1500	89	120-277V	TRIAC/0-10V	100°	50,000
				21	2000					
				26	2500					
	6"	LR22676	LED RMP6/3WO/5CCT/RD/WT/UNV/DD	19	1800	100	120-277V	TRIAC/0-10V	100°	50,000
25				2400						
32				3000						
SQUARE	3"	LR22679	LED RMP3/2WO/5CCT/SQ/WT/UNV/DD	9	750	80	120-277V	TRIAC/0-10V	90°	50,000
				12	1000					
	4"	LR22680	LED RMP4/3WO/5CCT/SQ/WT/UNV/DD	12	1000	87	120-277V	TRIAC/0-10V	90°	50,000
				15	1400					
				19	1800					
	5"	LR22682	LED RMP5/3WO/5CCT/SQ/WT/UNV/DD	16	1500	89	120-277V	TRIAC/0-10V	100°	50,000
				21	2000					
				26	2500					
	6"	LR22684	LED RMP6/3WO/5CCT/SQ/WT/UNV/DD	19	1800	100	120-277V	TRIAC/0-10V	100°	50,000
				25	2400					
32				3000						

PHOTOMETRIC

MODEL	DESCRIPTION	COLOR (CCT)	TEMP	CRI	ETL	ENERGY STAR	PLATE (KNOCKOUT)
LR22671	LED RMP3/2WO/5CCT/RD/WT/UNV/DD	2700K/3000K/3500K/4000K/5000K	CCT SELECT	80	YES	YES	LR41002 #0 LR41006 #1 LR41010 R0
LR22672	LED RMP4/3WO/5CCT/RD/WT/UNV/DD	2700K/3000K/3500K/4000K/5000K	CCT SELECT	80	YES	YES	LR41002 #1 LR41006 #3 LR41010 R1
LR22673	LED RMP5/3WO/5CCT/RD/WT/UNV/DD	2700K/3000K/3500K/4000K/5000K	CCT SELECT	80	YES	YES	LR41002 #2 LR41006 #5 LR41010 R3
LR22676	LED RMP6/3WO/5CCT/RD/WT/UNV/DD	2700K/3000K/3500K/4000K/5000K	CCT SELECT	80	YES	YES	LR41002 #2 LR41006 #5 LR41010 R3
LR22679	LED RMP3/2WO/5CCT/SQ/WT/UNV/DD	2700K/3000K/3500K/4000K/5000K	CCT SELECT	80	YES	YES	LR41002 #0 LR41006 #1 LR41010 R0
LR22680	LED RMP4/3WO/5CCT/SQ/WT/UNV/DD	2700K/3000K/3500K/4000K/5000K	CCT SELECT	80	YES	YES	LR41002 #1 LR41006 #3 LR41010 R1
LR22682	LED RMP5/3WO/5CCT/SQ/WT/UNV/DD	2700K/3000K/3500K/4000K/5000K	CCT SELECT	80	YES	YES	LR41002 #2 LR41006 #5 LR41010 R3
LR22684	LED RMP6/3WO/5CCT/SQ/WT/UNV/DD	2700K/3000K/3500K/4000K/5000K	CCT SELECT	80	YES	YES	LR41002 #2 LR41006 #5 LR41010 R3

TRIM REPLACEMENT OPTION

*SOLD SEPARATELY

3"



LR22650

LED RMP3/HO/5CCT/TRIM/RD/BK

4"



LR22652

LED RMP4/HO/5CCT/TRIM/RD/BK

5"



LR22654

LED RMP5/HO/5CCT/TRIM/RD/BK

6"



LR22656

LED RMP6/HO/5CCT/TRIM/RD/BK

DIMENSIONS

